

DIVERSITECH[®]
971KIT

SUPER SEAL SEALANT

TOTAL

AC/R STOP LEAK+ DRY R[®] & FLASH[™] DETECT

SMALL SYSTEMS | UP TO 5 KW
UP TO **1.5 TONS**


**AMERICA'S
BEST SELLING
STOP LEAK**



 **MADE IN USA**
VACUUM-SEALED 1 oz | 28 g

THIS END UP FOR CHARGING

ENSURE SYSTEM IS FULLY CHARGED WITH REFRIGERANT.

1. TURN UNIT OFF.

2. Confirm piercing pin is below washer and connect hose to cam.

3. Attach hose fitting to low side service port and then purge air from hose.

4. Turn valve handle clockwise to pierce can.

5. Turn valve handle counterclockwise to **CHARGE** can with refrigerant (can may get warm).

6. While inverted, **TURN UNIT ON** to empty can.

7. Once can is empty, remove hose fitting from low side service port.

NO RUNTIME REQUIRED



DANGER

Flammable liquid and vapor. Causes serious eye irritation. May cause an allergic skin reaction. May

cause damage to organs through repeated or prolonged exposure (bladder).

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves and eye protection. Wash hands thoroughly after handling. Do not breathe

vapor or spray.

In case of fire: Use carbon dioxide, dry chemical powder, alcohol-resistant foam or water spray to

extinguish. If in EYES: Rinse cautiously with water for several minutes. Remove contact lenses. If

ON SKIN: Remove contaminated clothing. Continue rinsing. If eye irritation persists: Get medical attention.

If ON HAIR: Take off immediately all contaminated clothing. Rinse skin with water/shower. Specific

treatment, see first aid measures on this label. If skin irritation or rash occurs: Get medical

attention. Take off contaminated clothing and wash it before reuse. Get medical attention if you feel

unwell.

Dispose of contents/container in accordance with local/regional/national regulations.

SDS available upon request. DO NOT EXCEED 300 PSI/20.7 BAR ON CAN

DiversiTech Corporation 6550 Sugarloaf Parkway Suite 100, Duluth, GA 30097
Telephone: 678.542.3500 Emergency Chemical Telephone: 1.800.255.3924



DDC140386

PN# 971KIT

Tech Hotline: 1.866.548.3644
www.diversitech.com

PROFESSIONAL HVAC/R USE ONLY

3.875 x 7