

DIRECT DRIVE PUMPS - WGFP-SERIES

Constructed with stainless steel, cast iron and durable thermoplastic, our solids-handling submersible water feature pumps meet the rigorous demands of the most impressive water features.



FEATURES

- Corrosion-resistant body
- Dual seals for added protection in larger models
- Heavy-duty, stainless steel motor housing
- Rated for continuous use if fully submerged
- Solids handling up to 1"




ORDERING INFORMATION



WGFP Series	Item No.	Amps	Watts	Volts	Cord (ft)	Submerged Use	Discharge FNPT	Gallons Per Hour (GPH) @ Height								Solids Diameter	Shut-off (ft)
								5'	10'	15'	20'	25'	30'	35'	40'		
WGFP-75	566069	8	847	115 V	19'	✓	2"	4890	4350	3750	3070	2262	-	-	-	1.38"	36
WGFP-100	566070	12	1210	115 V	19'	✓	2"	6400	5500	4700	3700	2500	-	-	-	1.35"	35
WGFP-150	566071	11	1210	115 V	19'	✓	3"	9750	8200	6500	4600	2200	-	-	-	0.75"	32
WGFP-200	566072	9	2085	230 V	32'	✓	3"	16000	15000	13410	11575	9775	7645	5610	3120	0.75"	45

DIMENSIONS

Dimensions (in)	A	B	C	D	E
WGFP-75	14.44	3.88	8.78	4.53	5.83
WGFP-100	17.35	4.05	10.29	5.18	6.30
WGFP-150	18.50	5.00	11.75	6.50	7.50
WGFP-200	20.31	5.13	11.71	5.96	7.50



PERFORMANCE



Note:

- Do not run dry
- Do not use with chlorine. Designed for freshwater or natural fountain cleaner use.
- Do not place pump directly on gravel, sand, or mud