

PRESSURE RELIEF VALVE

For use on all closed systems to prevent damage in the event of a malfunction due to some foreign object or matter becoming lodged in an automatic regulating or control valve. Featuring a pop-type relief action for maximum performance.



Figure No. 5660




Figure No.	Press. Set (PSI)	Dimensional Data (Inches)				
		Inlet	Outlet	A	B	C
5660	15-175	3/4	3/4	3	3	1
5661	175	1/2	1/2	1 3/4	1	15/16

3/4 Available with 3/4 Male or 3/4 female inlet with 3/4" Female Outlet

THREE WAY GAUGE VALVE

For use with Sprinkler System gauges.



Figure No. 5662

Standard Equipment:
1/4" valve NPT Bronze three way globe valve with handwheel. Female inlets. 175 PSI.

Figure No. 5662 Size 1/4

GLOBE VALVES RISING STEM

For use with Sprinkler System gauges.



Figure No. 5663-5670

Standard Equipment:
Bronze with teflon seat. 125 WSP.

Figure No.	Size
5663	1/4
5664	3/8
5665	1/2
5666	3/4
5667	1
5668	1 1/4
5669	1 1/2
5670	2

OPTIONAL FINISHES:
RC - Rough Chrome Plated

CAPS AND CHAINS

Used to cover and protect male outlet threads on valves and hydrants. Prevents entry of foreign matter.

CAST BRASS WITH CHAIN

Fig. No. With Pin Lugs	Fig. No. With Rocker Lugs	Size
5709	5710	1 1/2
5713	5714	2 1/2
5715	5716	3
5717	5718	4



Figure No. 5709-5713

OPTIONAL FINISHES:

PB - Polished Brass
RC - Rough Chrome Plated
PC - Polished Chrome Plated

SPECIFY THREAD

CAST HARDCOATED ALUMINUM CAP WITH CHAIN

Fig. No. 5720 Size 2 1/2

NY BSA/MEA Approved

PLASTIC CAP WITH CHAIN

Fig. No. 5721 Size 1 1/2
5722 Size 2 1/2
5723 Size 3

VALVE ESCUTCHEONS



Used to trim pipe into cabinet.

Figure No.	Size	Material
5730	1 1/2	Stamped Steel Cadmium Plated
5735	2 1/2	Stamped Steel Cadmium Plated

Figure No.	Size	Material
5750	1 1/2	Cast Brass
5755	2 1/2	Cast Brass

OPTIONAL FINISHES:

PB-- Polished brass
RC-- Rough Chrome Plated
PC-- Polished Chrome Plated

**SPECIFY FIGURE NO
SIZE-FINISH**