

Hand Seamers



Work. Perform. Outlast.
Limited Lifetime Warranty

Powerful Forged Steel Jaws!

Precise vee-notched depth graduations on jaws are in 1/4 in. (6.4 mm) increments.

Jaws are drop forged, high impact steel. Hardened steel handles resist abuse. Powerful compound leverage design. Tool also features rust resistant nickel plating.

3 in. Hand Seamer



S2R with vee-notched depth graduations at 6.4 mm increments. Ergonomic Redline Handles with unique one-hand operation latch offer maximum compound leverage performance and natural fit and feel.

6 in. Offset Hand Seamer



S3R is ideal for tight-working quarters or working overhead. The offset design keeps hands off work obstacles such as floor joists and underlayments.

6 in. Hand Seamer



S6R features wide 152 mm jaws that produce uniform, accurate bends in sheet steel and non-ferrous metals with greater control and efficiency. Wider jaws also minimize buckling and bowing of metal. Designed for all the metal trades, including HVACR installation, roofing, siding and commercial building and remodeling.



- Ergonomic Redline Handles with unique one-hand operation latch offer maximum compound leverage performance and natural fit and feel.
- Grip opening maximizes power range of human hand.
- Head-to-handle linkage increases user-applied leverage 7:1.
- Natural contours and non-slip cushion insert offer gripping power and control.
- Quick thumb latch.
- Metal handle frames will not collapse.



CAPACITIES	Material	Aluminum	Copper	Stainless Steel 26 Gauge	Galvanized Steel 24 Gauge	Mild Steel 24 Gauge
S5R / S9R	in. (mm)	0.029 (0.74)	—	—	—	—
S2R / S3R / S6R	in. (mm)	0.035 (0.89)	0.023 (0.58)	0.018 (0.46)	0.028 (0.71)	0.024 (0.61)

Replacement Spring for Hand Tools

5018 Fits All models on this page