


STANDARD FITTINGS

No. 30 – 45° Lateral

Size		No. 30 45° Lateral (SW)	
Nominal Size inches or mm	Actual Pipe Outside Diameter inches/mm	C to LE inches/mm	C to SE inches/mm
¾	1.050 26.9	4.50 114	2.00 51
1	1.315 33.7	5.00 127	2.25 57
1 ¼	1.660 42.4	5.75 146	2.50 64
1 ½	1.900 48.3	6.25 159	2.75 70
2	2.375 60.3	7.00 178	2.75 70
2 ½	2.875 73.0	7.75 197	3.00 76
76.1 mm	3.000 76.1	8.50 216	3.25 83
3	3.500 88.9	8.50 216	3.25 83
3 ½	4.000 101.6	10.00 254	3.50 89
4	4.500 114.3	10.50 267	3.75 95
5	5.563 141.3	12.50 318	4.00 102
165.1 mm	6.500 165.1	14.00 356	4.50 114
6	6.625 168.3	14.00 356	4.50 114
8	8.625 219.1	18.00 457	6.00 152
10	10.750 273.0	20.50 521	6.50 165
12	12.750 323.9	23.00 584	7.00 178
14 #	14.000 355.6	26.50 673	7.50 191
16 #	16.000 406.4	29.00 737	8.00 203
18 #	18.000 457.0	32.00 813	8.50 216
20 #	20.000 508.0	35.00 889	9.00 229
24 #	24.000 610.0	40.00 1016	10.00 254
14 – 24	AGS For AGS fitting information, refer to the AGS fittings section.		



No. 30

For use on cut grooved systems only. For roll grooved systems, Victaulic offers the Advanced Groove System (AGS).

NOTE: All fittings are ductile iron unless noted otherwise with an “sw” or “s”.
SW = Segmentally Welded, S = Carbon Steel

 Always refer to the current Victaulic submittal publication in the G-100 General Catalog or on the website www.victaulic.com for the most up-to-date dimensional information.

