



## Remote Water Chiller R8, R12

### Suggested Specification

Remote drinking water chiller shall deliver at least 8.0 gph of water at 500F cooled from 800F ambient. Evaporator shall be high efficiency tank type and shall be encapsulated in insulation. R-134a refrigerant system shall be hermetically sealed and refrigerant flow shall be capillary tube controlled. Cabinet finish shall be galvanized steel. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with ANSI/NSF 61 and NSF/ANSI 372.

### Models

- R8 delivers 8.0 gallon of chilled water per hour
- R12 delivers 12.0 gallons of chilled water per hour

### Standard Features

- Built-in 100 micron strainer stops particles before they enter the waterway
- Waterways are Lead-Free in materials & construction
- Heavy gauge galvanized steel
- High efficiency cooling system
- Refrigerant R-134a
- Not for use with RO water

### Finishes

- Standard cabinet finish: Galvanized steel

### Installation

- Wall mounting cradle and stainless steel ventilating grille are available at extra cost for in wall installation
- Shipped with complete instructions and wall mounting bracket

### Options (at additional cost)

- Wall mounting cradle and stainless steel (030101-001)
- Shelf support (026929)

### Limited 5-Year Warranty

(Continental limits of the United States and Canada)  
Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

### Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

### Certifications/Compliance

- Oasis International Electric Water Coolers are listed by Underwriters Laboratories Inc. and comply with both U.S. and Canadian Requirements.
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.
- This unit complies with ARI standard 1010 Testing, Operating and Rating requirements (electric water coolers only).
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed.



Model	50° F Drinking Water 90° F Ambient Air Temp*			Hot'N Cold Model	115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx
	Rated Capacity GHP	Base Rate GHP	Pre-Cooler		Compr. HP	Full Load Amps	Rated Watts			
R8	8.0		N/A		1/4	4.8	550		N/A	52 Lbs
R12	12.0		N/A		1/3	5.4	620		N/A	52 lbs

\* Industry Standard Rating Condition 80° F inlet water temperature

Specifications subject to change without notice

# OASIS® REMOTE COOLING UNIT R8, R12

