

ProPEX® Lead-free (LF) Brass Stop Valve

Submittal information

Revision C: March 24, 2017

Project information

Job name:

Location:

Engineer:

Contractor:

Manufacturer's representative:

Part no. ordered:

Date submitted:

Submitted by:

Approved by:

Technical data

Material: Chrome-plated C69300 brass

Maximum working pressure/temperature: 145 psi (10 bar)/194°F (90°C)

Product information and application use

Uponor ProPEX® lead-free (LF) brass stop valves are quarter-turn, chrome-plated and available in either angle or straight-stop configurations.¹

Made for point-of-use shut-off at the fixture, this stop valve connects ½" Uponor AquaPEX® tubing to ⅜" outside diameter (O.D.) risers.



✓	Description	Part number	Length	Depth	Valve threading	Weight
	ProPEX LF Angle Stop Valve for ½" PEX	LF4855038	2.02"	1.32"	⅜" compression	0.16 lbs.
	ProPEX LF Straight Stop Valve for ½" PEX	LF4865038	1.97"	1.33"	⅜" compression	0.16 lbs.

Installation

Install this straight or angle stop valve according to your local building code. Do not dismantle. Refer to the AquaPEX Professional Plumbing Installation Guide or Radiant Floor Heating Installation Handbook for additional information.

Standards

CSA B137.5 and B125; ASTM F877; ASTM F1960; ASME A112.18.1

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

ANSI/NSF 14- and 61-certified; U.P. Code, Annex G

Related applications

PEX-a plumbing systems

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
T 800.321.4739
F 952.891.2008
uponorpro.com

Uponor Ltd.
2000 Argentia Rd., Plaza 1, Ste. 200
Mississauga, ON L5N 1W1 CANADA
T 888.994.7726
F 800.638.9517
uponorpro.com

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor, Ltd.