

Rev. 4-14 Shaded area indicates changes

3/4" - 2" MUELLER[®] 300™ BALL CORPORATION VALVES

B-25008N	MUELLER [®] 300 [™] Ball Corporation Valve Inlet: AWWA taper (MUELLER "CC") thread Outlet: MUELLER [®] 110 [®] Conductive Compression Connection for CTS O.D* tubing	B-25028N	MUELLER [®] 300 [™] Ball Corporation Valve Inlet: AWWA I.P. thread Outlet: MUELLER [®] 110 [®] Conductive Compression Connection for CTS O.D. tubing
3/4" 3/4" x 1" 1"	1-1/2" 1-1/2" x 2" 2"	3/4" 3/4" x 1" 1"	1-1/2" 1-1/2" x 2" 2"
B-25009N	MUELLER 300 Ball Corporation Valve Inlet: AWWA taper (MUELLER "CC") thread Outlet: MUELLER [®] 110 [®] Compression Connection for IPS PE* pipe	B-25029N	MUELLER 300 Ball Corporation Valve Inlet: AWWA I.P. thread Outlet: MUELLER 110 [®] Compression Connection for IPS PE* pipe
3/4" 3/4" >	1" 1"	3/4" 3/4" x	1" 1"
E-25009N	MUELLER 300 Ball Corporation Valve Inlet: AWWA taper (MUELLER "CC") thread Outlet: MUELLER Pack Joint for IPS PE* pipe **Note: 3/4" size only may also be used on PVC	E-25029N	MUELLER 300 Ball Corporation Valve Inlet: AWWA I.P thread Outlet: MUELLER Pack Joint for IPS PE* pipe **Note: 3/4" size only may also be used on PVC
3/4"** 1"	1-1/2" 2"	3/4"** 1"	1-1/2" 2"
V-25056N	MUELLER 300 Ball Corporation Valve Inlet: AWWA taper (MUELLER "CC") thread Outlet: MUELLER Pack Joint for IPS PVC* pipe	V-25058N	MUELLER 300 Ball Corporation Valve Inlet: AWWA I.P thread Outlet: MUELLER Pack Joint for IPS PVC* pipe
1" 1-1/2	2"	1" 1-1/2	." 2"
P-25008N	MUELLER 300 Ball Corporation Valve Inlet: AWWA taper (MUELLER "CC") thread Outlet: MUELLER Pack Joint Connection for CTS O.D. * tubing	P-25028N	MUELLER 300 Ball Corporation Valve Inlet: AWWA I.P. thread Outlet: MUELLER Pack Joint Connection for CTS O.D.* tubing
3/4" 3/4"x1" 1"	1-1/2" 1-1/2"x2" 2"	3/4" 3/4" x 1" 1"	1-1/2" 1-1/2" x 2"‡ 2"
*See charts on pages 5.12-5.16 fc	r tubing and pipe that may be used with these c	onnections.	

*See charts on pages 5.12-5.16 for tubing and pipe that may be used with these connections. NOTE: Sizes shown above represent nominal size of inlet and outlet connections. When two sizes are given, the first is size of inlet and the second is size of outlet. ‡ Requires minimum ordering quantity. Contact MUELLER Customer Service Center for minimum order requirements and availability.

MUELLER Corporation Valves are manufactured and tested in accordance with ANSI/AWWA C800. Components in contact with potable water will also comply with latest requirements of the Federal Safe Drinking Water Act.