


Victaulic Aquamine® Products


SERIES 2900

SERIES 2904 FEMALE X FEMALE COUPLING (ALF X ALF)




Size	Pressure Rating	L	O.D.	Weight
Nominal Size Inches mm	PSI kPa	Inches mm	Inches mm	Lbs. kg
2	250	5.25	3.20	0.9
50	1724	133.35	81.28	0.4
3	250	7.25	4.38	1.9
80	1724	184.15	111.25	0.9
4	250	8.25	5.47	3.1
100	1724	209.55	138.94	1.4
4 HP	350	8.25	6.00	5.0
100	2413	209.55	152.40	2.3
6	250	8.25	7.84	5.6
150	1724	209.55	199.14	2.5
6 HP	350	8.25	8.72	10.5
150	2413	209.55	221.49	4.8
8	200	9.50	10.19	11.1
200	1379	241.30	258.83	5.0
8	250	9.50	10.19	11.1
200	1724	241.30	258.83	5.0
8 HP	350	9.50	10.75	15.2
200	2413	241.30	273.05	6.9
10	160	12.00	12.44	18.0
250	1103	304.80	315.98	8.2
12	160	12.00	14.65	24.2
300	1103	304.80	372.11	11.0

SERIES 2905 FEMALE X SOLVENT CEMENT (FEMALE) COUPLING (ALF X SCF)



Size	Pressure Rating	L	O.D.	Weight
Nominal Size Inches mm	PSI kPa	Inches mm	Inches mm	Lbs. kg
2	250	5.50	3.20	1.0
50	1724	139.7	81.28	0.5
3	250	8.00	4.38	2.2
80	1724	203.2	111.25	1.0
4	250	9.00	5.47	3.4
100	1724	228.6	138.94	1.5
6	250	9.00	7.84	6.3
150	1724	228.6	199.14	2.9
8	200	10.00	10.19	12.2
200	1379	254.0	258.83	5.5
10	160	12.00	12.44	18.7
250	1103	304.8	315.98	8.5
12	160	12.00	14.65	24.7
300	1103	304.8	372.11	11.2

SERIES 2906 AQUAMINE GROOVE X SOLVENT CEMENT (ALM X PEM)



Size	Pressure Rating	L	O.D.	Weight
Nominal Size Inches mm	PSI kPa	Inches mm	Inches mm	Lbs. kg
2	250	7.00	2.375	0.5
50	1724	177.8	60.33	0.2
3	250	9.00	3.50	1.4
80	1724	228.6	88.90	0.6
4	250	10.00	4.50	2.4
100	1724	254.0	114.30	1.1
6	250	12.00	6.625	5.5
150	1724	304.8	168.28	2.5
8	200	13.00	8.625	9.3
200	1379	330.2	219.08	4.2
10	160	16.00	10.750	14.2
250	1103	406.4	273.05	6.4
12	160	16.00	12.750	20.0
300	1103	406.4	323.85	9.1