


Victaulic Aquamine® Products


SERIES 2900

SERIES 2907 AQUAMINE GROOVE X ORIGINAL VICTAULIC GROOVE (ALM X VIC)




Size	Pressure Rating	Material	L	O.D.	Weight
Nominal Size Inches mm	PSI kPa		Inches mm	Inches mm	Lbs. kg
2	250	PVC	7.00	2.375	0.5
50	1724		177.8	60.33	0.2
3	250	PVC	9.00	3.500	1.4
80	1724		228.6	88.90	0.6
4	240	PVC	10.00	4.500	2.4
100	1655		254.0	114.30	1.1
4 HP	350	Steel	9.00	4.500	5.5
100	2413		228.6	114.30	2.5
6	160	PVC	12.00	6.625	5.5
150	1103		304.8	168.28	2.5
6 HP	350	Steel	10.00	6.625	10.0
150	2413		254.0	168.28	4.5
8	120	PVC	13.00	8.625	9.3
200	827		330.2	219.08	4.2
8 HP	350	Steel	10.00	8.625	14.5
200	2413		254.0	219.08	6.6
10	100	PVC	16.00	10.750	14.2
250	689		406.4	273.05	6.4
12	80	PVC	16.00	12.750	20.0
300	552		406.4	323.85	9.1

SERIES 2908 AQUAMINE GROOVE X MALE THREAD NIPPLE (ALM X NPT-M)



Size	Pressure Rating	L	O.D.	Weight
Nominal Size Inches mm	PSI kPa	Inches mm	Inches mm	Lbs. kg
2	200	7.00	2.375	0.5
50	1379	177.8	60.33	0.2
3	190	9.00	3.500	1.4
80	1310	228.6	88.90	0.6
4	160	10.00	4.500	2.4
100	1103	254.0	114.30	1.1
6	140	12.00	6.625	5.5
150	965	304.8	168.28	2.5
8	120	13.00	8.625	9.3
200	827	330.2	219.08	4.2
10	120	16.00	10.750	14.2
250	827	406.4	273.05	6.4
12	110	16.00	12.750	20.0
300	758	406.4	323.85	9.1

SERIES 2909 SOLVENT-CEMENT X MALE THREAD NIPPLE (PEM X NPT-M)



Size	Pressure Rating	L	O.D.	Weight
Nominal Size Inches mm	PSI kPa	Inches mm	Inches mm	Lbs. kg
2	200	5.25	2.375	0.5
50	1379	133.35	60.33	0.2
3	190	6.50	3.500	1.4
80	1310	165.10	88.90	0.6
4	160	7.00	4.500	2.4
100	1103	177.80	114.30	1.1
6	140	9.00	6.625	5.5
150	965	228.6	168.28	2.5
8	120	10.40	8.625	9.3
200	827	264.16	219.08	4.2
10	120	16.00	10.750	14.2
250	827	406.40	273.05	6.4
12	110	16.00	12.750	20.0
300	758	406.40	323.85	9.1