

M18 FUEL

3/8" Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2758-22, 2758-22CT (2758-20 Tool-Only)

Specifications:

Fastening Torque	210 ft-lbs
Nut-Busting Torque	210 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode (Customizable)
Anvil Type	3/8" Friction Ring
Length / Weight	5.9" / 4.2 lbs

Includes: 2758-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2758-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; **All Kits Include:** Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18 FUEL

3/8" Compact Impact Wrench w/ Friction Ring Kit

2754-22, 2754-22CT (2754-20 Tool-Only)

Specifications:

Fastening Torque	210 ft-lbs
Nut-Busting Torque	210 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode
Anvil Type	3/8" Friction Ring
Length / Weight	5.9" / 4.2 lbs

Includes: 2754-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2754-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; **All Kits Include:** Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18™ 3/8" Compact Impact Wrench Kit

2658-22, 2658-22CT (2658-20 Tool-Only)

Specifications:

Fastening Torque	167 ft-lbs
Nut-Busting Torque	167 ft-lbs
IPM	0 – 3,350
RPM	0 – 2,450
Anvil Type	3/8" Friction Ring
Length / Weight	6.0" / 4.1 lbs

Includes: 2658-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs; 2658-22CT (2) M18™ REDLITHIUM™ CP1.5 Battery Packs; **All Kits Include:** Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" Mid-Torque Impact Wrench w/ Pin Detent Kit

2860-22 (2860-20 Tool-Only)

Specifications:

Fastening Torque	450 ft-lbs
Nut-Busting Torque	600 ft-lbs
IPM	0 – 3,000
RPM	0 – 2,400
Anvil Type	1/2" Pin Detent
Length / Weight	6.7" / 5.3 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" Mid-Torque Impact Wrench w/ Friction Ring Kit

2861-22 (2861-20 Tool-Only)

Specifications:

Fastening Torque	450 ft-lbs
Nut-Busting Torque	600 ft-lbs
IPM	0 – 3,000
RPM	0 – 2,400
Anvil Type	1/2" Friction Ring
Length / Weight	6.7" / 5.3 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

3/8" Mid-Torque Impact Wrench w/ Friction Ring Kit

2852-22, 2852-22CT (2852-20 Tool-Only)

Specifications:

Fastening Torque	450 ft-lbs
Nut-Busting Torque	600 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,300
DRIVE CONTROL™	3-Mode
Anvil Type	3/8" Friction Ring
Length / Weight	6.7" / 5.3 lbs

Includes: 2852-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2852-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; **All Kits Include:** Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1" High Torque Impact Wrench w/ ONE-KEY™ Kit

2867-22 (2867-20 Tool-Only)

Specifications:

Fastening Torque	1,500 ft-lbs
Nut-Busting Torque	1,800 ft-lbs
IPM	0 – 2,450
RPM	0 – 1,650
DRIVE CONTROL™	4 Modes (Customizable)
Length / Weight	10.9" / 12.9 lbs

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Packs, (1) Tool-Free Adjustable Handle, (1) Lanyard Loop, Rapid Charger, Contractor Bag



M18 FUEL

3/4" High Torque Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2864-22 (2864-20 Tool-Only)

Specifications:

Fastening Torque	1,200 ft-lbs
Nut-Busting Torque	1,600 ft-lbs
IPM	0 – 1,850
RPM	0 – 1,850
DRIVE CONTROL™	4 Modes (Customizable)
Length / Weight	8.6" / 7.9 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18™ 3/4" High Torque Impact Wrench w/ Friction Ring Kit

2664-22 (2664-20 Tool-Only)

Specifications:

Fastening Torque	525 ft-lbs
Breakaway Torque	700 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Anvil Type	3/4" Friction Ring
Length / Weight	9.0" / 6.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" Ext. Anvil Controlled Torque Impact Wrench w/ ONE-KEY™ Kit

2769-22 (2769-20 Tool-Only)

Specifications:

Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 – 2,400
RPM	0 – 1,800
DRIVE CONTROL™	4-Modes (Customizable)
Anvil Type	1/2" Friction Ring
Length / Weight	10.1" / 5.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Contractor Bag



M18 FUEL

1/2" High Torque Impact Wrench w/ Pin Detent w/ ONE-KEY™ Kit

2862-22 (2862-20 Tool-Only)

Specifications:

Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 – 2,400
RPM	0 – 1,800
DRIVE CONTROL™	4-Modes (Customizable)
Anvil Type	1/2" Pin Detent
Length / Weight	8.1" / 7.2 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" High Torque Impact Wrench w/ Pin Detent Kit

2766-22 (2766-20 Tool-Only)

Specifications:

Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 – 2,400
RPM	0 – 1,850
DRIVE CONTROL™	4-Modes w/ Bolt Removal Mode
Anvil Type	1/2" Pin Detent
Length / Weight	8.1" / 7.1 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18™ 1/2" High Torque Impact Wrench w/ Pin Detent Kit

2662-22 (2662-20 Tool-Only)

Specifications:

Fastening Torque	450 ft-lbs
Breakaway Torque	640 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Anvil Type	1/2" Pin Detent
Length / Weight	8.9" / 6.7 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" High Torque Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2863-22 (2863-20 Tool-Only)

Specifications:

Fastening Torque	1,000 ft-lbs
Nut-Busting Torque	1,400 ft-lbs
IPM	0 – 2,100
RPM	0 – 1,750
DRIVE CONTROL™	4-Modes (Customizable)
Anvil Type	1/2" Friction Ring
Length / Weight	8.4" / 7.6 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" High Torque Impact Wrench w/ Friction Ring Kit

2767-22 (2767-20 Tool-Only)

Specifications:

Fastening Torque	1,000 ft-lbs
Nut-Busting Torque	1,400 ft-lbs
IPM	0 – 2,100
RPM	0 – 1,750
DRIVE CONTROL™	4-Modes w/ Bolt Removal Mode
Anvil Type	1/2" Friction Ring
Length / Weight	8.4" / 7.5 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

