

SeeSnake® Reels and Cameras



SeeSnake rM200

rM200 D2A Drum
Catalog No. 47548rM200B Reel
Catalog No. 47528

RIDGID® SEESNAKE RM200 MAX

With its stow bin and transport system, the SeeSnake rM200 MAX camera system was designed with convenience and ergonomics in mind. The rM200 provides different combinations of push cable stiffness and spring flexibility.

FEATURES

- Interchangeable drum system for on-the-job flexibility.
- Ergonomic handle and wheels for easy transport to and from the job site.
- Provides a convenient docking system for SeeSnake CS6x and CS65x monitors.
- Includes pipe guides for better in-pipe imaging and a stow bin for storing tools at the job site.



D2A Best Use: The rM200 D2A configuration uses a moderately stiff 200' (61 m) push cable that provides a good compromise between cable stiffness and ability to navigate turns in the pipe.



D2B Best Use: The rM200 D2B includes 165' (50 m) of our stiffest push cable, coupled with a dual-nested spring to navigate tight corners that are not usually passable with such a stiff cable.

SPECIFICATIONS

| | SeeSnake Max rM200 | |
|-----------------------------|------------------------------|-----------------------------|
| | D2A | D2B |
| Rated Pipe Capacity | 1.5" to 8" (38 mm to 203 mm) | 2" to 8" (51 mm to 203 mm) |
| CABLE | | |
| Max Cable Length | 200' (61 m) | 165' (50 m) |
| Minimum Bend Radius | 2.8" (70 mm) | 3.5" (89 mm) |
| CAMERA | | |
| Style | Self-Leveling | Self-Leveling |
| Diameter | 1" (25 mm) | 1" (25 mm) |
| Length | 1" (25 mm) | 1" (25 mm) |
| SONDE | | |
| Frequency | 512 Hz | 512 Hz |
| Type | Flexmitter | Flexmitter |
| DISTANCE MEASUREMENT | | |
| Type | Built-in with Video Overlay | Built-in with Video Overlay |
| Data Communication | Two-Way | Two-Way |

| Catalog No. | Description | Weight | |
|-------------|--------------------------------------|--------|------|
| | | lb | kg |
| 43248 | Reel, SeeSnake MAX rM200A w/D2A Drum | 36.4 | 16.5 |
| 47548 | Reel, SeeSnake MAX rM200B w/D2B Drum | 39.2 | 17.8 |

Accessories

| Catalog No. | Description |
|-------------|--|
| 47793 | 36 mm Camera Head, 25mm Camera, Pkg of 1 |
| 35338 | 45 mm Pipe Guide, 25mm Camera, Pkg of 2 |
| 97462 | 60 mm Pipe Guide, 25mm Camera, Pkg of 6 |
| 46708 | 85 mm Pipe Guide, 25mm Camera, Pkg of 2 |
| 46713 | 125 mm Pipe Guide, 25mm Camera, Pkg of 2 |
| 17553 | Spanner Wrench, 25 mm |
| 44038 | rM200 Stow Bins |
| 47548 | Drum, rM200 D2A NTSC |
| 47538 | Drum, rM200 D2B NTSC |

Replacement Parts

| Catalog No. | Description |
|-------------|------------------------------|
| 43138 | RM200 Camera |
| 43863 | 200' SeeSnake D2A Push Cable |
| 51813 | 165' SeeSnake D2B Push Cable |
| 33108 | Interconnect Cable |

SeeSnake® Reels and Cameras – Compact Series

NEW
COMING IN 2019



SeeSnake Compact M40 with
docked CS6xPak



RIDGID® SEESNAKE COMPACT M40 WITH TRUSENSE™

The Compact M40 offers similar performance to the SeeSnake Mini in the popular Compact form-factor, combining a small package and all-in-one monitor capability (when used with the SeeSnake CS6xPak monitor). The Compact M40 features TruSense™ technology.



Best Use: The Compact M40 has 131' (40 m) of moderately stiff push cable, providing a good compromise between stiffness and the ability to navigate turns.

FEATURES

- Quick-release docking system for fast, efficient job setup with the SeeSnake CS6xPak monitor.
- Sturdy metal frame provides a solid base that makes it easy to push and retrieve the cable.
- Powerful Flexmitter® sonde has longer range and preserves the camera's ability to make turns.
- High dynamic range (HDR) image sensor offers bright, clear in-pipe imaging in difficult lighting conditions.
- TiltSense Sensor displays the camera's pitch in a pipe on a connected SeeSnake CSx series monitor.
- Included pipe guides center the camera for better in-pipe imaging.

SPECIFICATIONS

| | SeeSnake Compact M40 |
|-----------------------------|------------------------------|
| Rated Pipe Capacity | 1.5" to 8" (38 mm to 203 mm) |
| CABLE | |
| Max Cable Length | 131.2' (40 m) |
| Minimum Bend Radius | 3" (76 mm) |
| CAMERA | |
| Style | Self-Leveling TruSense |
| Diameter | 1" (25 mm) |
| Length | 1" (25 mm) |
| SONDE | |
| Frequency | 512 Hz |
| Type | Flexmitter |
| DISTANCE MEASUREMENT | |
| Type | TruSense Counter |
| Data-Enabled | Two-Way |

| Catalog No. | Description | Weight | |
|-------------|--|--------|------|
| | | lb | kg |
| 63818 | SeeSnake Compact M40 System with 1 Battery and 1 Charger | 31.5 | 14 |
| 63813 | SeeSnake Compact M40 System | 27.7 | 12.5 |
| 63673 | SeeSnake Compact M40 (Reel Only) | 22 | 9.9 |

Accessories

| Catalog No. | Description |
|-------------|--|
| 47793 | 36 mm Pipe Guide, 25 mm Camera, Pkg of 1 |
| 35338 | 45 mm Pipe Guide, 25mm Camera, Pkg of 2 |
| 97462 | 60 mm Pipe Guide, 25mm Camera, Pkg of 6 |
| 46708 | 85 mm Pipe Guide, 25mm Camera, Pkg of 2 |
| 46713 | 125 mm Pipe Guide, 25mm Camera, Pkg of 2 |
| 63868 | Various Pipe Guides, 25mm Camera Head |
| 17553 | Spanner Wrench, 25 mm |
| 56813 | CS6xPak Digital Recording Monitor |
| 57143 | CS6xPak with 2 Batteries and 1 Charger |
| 45363 | AC Battery Adapter |
| 44693 | 18 V Advanced Lithium 2.0 Ah Battery |
| 44698 | 18 V Advanced Lithium 4.0 Ah Battery |
| 43458 | 18 V Advanced Lithium Battery Charger |

Replacement Parts

| Catalog No. | Description |
|-------------|--|
| 63853 | 25 mm Self-Leveling Camera Head - TruSense |
| 63858 | 130' SeeSnake Compact M40 Push Cable |
| 24703 | Kickstand |
| 33108 | Interconnect Cable |

SeeSnake® Reels and Cameras – Compact Series

NEW
COMING IN 2019



SeeSnake Compact C40
with docked CS6xPak



RIDGID® SEESNAKE COMPACT C40 WITH TRUSENSE™

The Compact C40 comes in the popular Compact form-factor, combining a small package and all-in-one monitor capability (when used with the SeeSnake CS6xPak monitor). The Compact C40 features TruSense™ technology.



Best Use: The Compact C40 has 131' (40 meters) of flexible push cable, providing good ability to fit in smaller diameter pipes and navigate turns.

FEATURES

- Quick-release docking system for fast, efficient job setup with the SeeSnake CS6xPak.
- Sturdy metal frame provides a solid base that makes it easy to push and retrieve the cable.
- Powerful FleXmitter® sonde has longer range and preserves the camera's ability to make turns.
- High dynamic range (HDR) image sensor offers bright, clear in-pipe imaging in difficult lighting conditions.
- TiltSense Sensor displays the camera's degree of a tilt on a connected SeeSnake CSx series monitor.
- Included pipe guides center the camera for better in-pipe imaging.

SPECIFICATIONS

| SeeSnake Compact C40 | |
|-----------------------------|---------------------------------|
| Rated Pipe Capacity | 1.5" to 6" (38 mm to 152 mm) |
| CABLE | |
| Max Cable Length | 131.2' (40 m) |
| Minimum Bend Radius | 2.5" (64 mm) |
| CAMERA | |
| Style | Self-Leveling TruSense |
| Diameter | 1" (25 mm) |
| Length | 1" (25 mm) |
| SONDE | |
| Frequency | 512 Hz |
| Type | FleXmitter |
| DISTANCE MEASUREMENT | |
| Type | Data-Enabled Integrated Counter |
| Data Communication | Two-Way |

| Catalog No. | Description | Weight | |
|-------------|--|--------|------|
| | | lb | kg |
| 63828 | SeeSnake Compact C40 System with 1 Battery and 1 Charger | 27.1 | 12.3 |
| 63823 | SeeSnake Compact C40 System | 23.3 | 10.5 |
| 63668 | SeeSnake Compact C40 (Reel Only) | 17.6 | 8 |

Accessories

| Catalog No. | Description |
|-------------|---|
| 47793 | 36 mm Pipe Guide, 25 mm Camera, Pkg of 1 |
| 35338 | 45 mm Pipe Guide, 25 mm Camera, Pkg of 2 |
| 97462 | 60 mm Pipe Guide, 25 mm Camera, Pkg of 6 |
| 46708 | 85 mm Pipe Guide, 25 mm Camera, Pkg of 2 |
| 46713 | 125 mm Pipe Guide, 25 mm Camera, Pkg of 2 |
| 63868 | Various Pipe Guides, 25 mm Camera Head |
| 17553 | Spanner Wrench, 25 mm |
| 56813 | CS6xPak Digital Recording Monitor |
| 57143 | CS6xPak with 2 Batteries and 1 Charger |
| 45363 | AC Battery Adapter |
| 44693 | 18 V Advanced Lithium 2.0 Ah Battery |
| 44698 | 18 V Advanced Lithium 4.0 Ah Battery |
| 43458 | 18 V Advanced Lithium Battery Charger |

Replacement Parts

| Catalog No. | Description |
|-------------|--|
| 63858 | 25 mm Self-Leveling Camera Head - TruSense |
| 63863 | 130' SeeSnake Compact C40 Push Cable |
| 24703 | Kickstand |
| 33108 | Interconnect Cable |