

Features

- End drain.
- Slotted overflow for deep soaking.
- Integral lumbar support.
- 65-7/8" (1673 mm) x 32-5/16" (821 mm) x 18" (457 mm)

Material

- Cast iron with Safeguard® finish.

Installation

- Under-mount

Required Accessories

K- 7271 Brass Slotted Overflow Bath Drain

or

K- 7272 PVC Slotted Overflow Bath Drain

Recommended Accessories

K- 1172 Adjustable Feet



Codes/Standards

ASME A112.19.1/CSA B45.2

ASTM F462

KOHLER® Lifetime Limited Warranty for Cast Iron Components


See website for detailed warranty information.

Available Color/Finishes



Color tiles intended for reference only.

Color	Code	Description
-------	------	-------------

	0	White
	96	Biscuit



No change in measurements if connected with drain illustrated. (K-7271 or K-7272)



Technical Information

All product dimensions are nominal.

Installation:	Under-mount
Drain location:	End
Basin area, bottom:	45-3/4" x 21-3/8" (1162 mm x 543 mm)
Basin area, top:	53-7/8" x 25-1/8" (1368 mm x 638 mm)
Weight:	360 lbs (163.3 kg)
Minimum floor load:	61 lbs/ft ² (297.8 kg/m ²)
Water depth:	13-7/8" (352 mm)
Water capacity:	61 gal (230.9 L)
Template:	Under-mount, 1106074-7, required, included

Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.