


# DIMENSIONAL SPECIFICATIONS

LEAD-FREE IMPORT BRASS FITTINGS\* 125 LB.


## 45 DEGREE ELBOW

Part #	Size (IN.)	Approx. Net WT. (LB.)	A	B
XNL102-02	1/8	0.08	0.43	0.43
XNL102-04	1/4	0.11	0.55	0.55
XNL102-06	3/8	0.12	0.63	0.63
XNL102-08	1/2	0.25	0.79	0.79
XNL102-12	3/4	0.34	0.91	0.91
XNL102-16	1	0.54	1.07	1.07
XNL102-20	1-1/4	0.90	1.23	1.23
XNL102-24	1-1/2	1.03	1.31	1.31
XNL102-32	2	1.54	1.47	1.47
XNL102-40	2-1/2	3.30	1.98	1.98
XNL102-48	3	3.52	2.18	2.18
XNL102-64	4	8.01	2.62	2.62



## 45 DEGREE STREET ELBOW

Part #	Size (IN.)	Approx. Net WT. (LB.)	A	B	C	D
XNL103A-02	1/8	0.06	0.26	0.43	0.28	0.79
XNL103A-08	1/2	0.29	0.45	0.79	0.45	1.07
XNL103A-12	3/4	0.31	0.52	0.91	0.50	1.23
XNL103A-16	1	0.52	0.60	1.07	0.58	1.42
XNL103A-20	1-1/4	0.06	0.67	1.23	0.67	1.65
XNL103A-24	1-1/2	0.97	0.70	1.31	0.75	1.83
XNL103A-32	2	2.04	0.76	1.47	0.78	2.14



\*Conforms with lead content requirements for lead-free plumbing as defined by the U.S. Safe Drinking Water Act. Certified <0.25 weighted average % lead.

# MERIT BRASS

DIRECTING THE FLOW OF *Quality*