


FlameGuard® Technical  
**FlameGuard® Product Weights & Dimensions**



**Female Adapter - Special Reinforced Plastic Thread Style**


Socket x SR Fipt - Stainless Steel Collar  
 NSF® Certified Lead-Free



Part Number	Size	L	M	M1	N	Approx. Wt. (Lbs.)
4235-007SR	3/4	1- 7/8	1-13/32	1- 3/8	3/32	.08
4235-010SR	1	2- 5/32	1-23/32	1- 11/16	3/32	.12
4235-012SR	1-1/4	2- 5/16	2- 1/8	2- 1/16	3/16	.20

**Transition Male Adapter with Brass Thread**


Mipt x Socket  
 NSF® Certified Lead-Free



Part Number	Size	L	M1	N	Approx. Wt. (Lbs.)
4236-007	3/4	2-17/32	1-13/32	13/16	.28
4236-010	1	2-15/16	1-23/32	29/32	.44
4236-012	1-1/4	3- 1/8	2- 3/32	31/32	.68
4236-015	1-1/2	3- 9/32	2-11/32	31/32	.81
4236-020	2	3- 7/16	2-27/32	1	1.09

**TorqueSafe™ Female Spigot Sprinkler Head Adapters - Gasket Sealed Brass Thread Insert Style**

Spigot x Gasket Fipt  
 With Elastomer Seal - Use NO Thread Sealant



Part Number	Size	L	M	N	Approx. Wt. (Lbs.)
4238-101 G	3/4X1/2	1-15/16	1- 3/8	1-17/32	.14
4238-130 G	1X1/2	2- 1/16	1- 3/8	1-21/32	.15

**Not intended to convey or dispense water for human consumption through drinking or cooking**