## **MANUAL**





## 895-317GN2AABCP

Deck Mounted - 4" Centers

### PRODUCT TYPE

Deck mounted 4" centerset faucet

### FEATURES & SPECIFICATIONS

- Polished chrome plated finish
- Solid brass construction
- ECAST design provides durable brass construction with total lead content less than 0.25% by weighted average
- Rigid valve bodies
- 5 1/4" C-C Rigid/Swing field convertible gooseneck spout, threaded end, catalog #GN2A
- 4" Wristblade metal handles with eight point tapered broach and secured color coded index buttons, catalog #317
- Quaturn™ quarter-turn renewable compression cartridge that closes with water pressure with tapered square broach to facilitate handle removal, catalog #1-100XT and #1-099XT
- 1/2" NPSM supply inlets with coupling nuts for 3/8" or 1/2" flexible risers
- Mounting hardware included

#### PERFORMANCE SPECIFICATION

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140° F

## WARRANTY


- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

## **COMPLIANT TO**

- California Lead Plumbing Law (AB1953)
- NSF 61, Sec. 9
- ASME A112.18.1

• CSA B125

ADA










# 895-317GN2AABCP


CHICAGO FAUCETS a Geberit company

Deck Mounted - 4" Centers

### **ARCHITECT/ENGINEER SPECIFICATION**

Chicago Faucets No. 895-317GN2AABCP, Polished chrome plated solid brass construction. ECAST<sup>™</sup> construction with less than 0.25% lead content by weighted average. 5 3/8" C-C rigid/swing field convertible gooseneck spout with threaded end. 4" Wristblade handles with eight point tapered broach and secured color coded index buttons. Quaturn<sup>™</sup> quarter-turn renewable compression cartridge designed to close with water pressure with square tapered broach feature to help facilitate handle removal. Inlet shanks contain standard 1/2" NPSM threaded inlets with coupling nuts for connection to 3/8" or 1/2" standard flexible risers. Mounting hardware included. This product meets ADA requirements and is tested and certified to industry standards: ASME A112.18.1, NSF 61, Sec. 9, CSA B125 and California Lead Plumbing Law (AB1953).





#### OPERATION AND MAINTENANCE

Installation should be in accordance with local plumbing codes. Flush all pipes thoroughly before installation. After installation, remove spout outlet or flow control and flush faucet thoroughly to clear any debris. Care should be taken when cleaning this product. Do not use abrasive cleaners, chemicals or solvents as they can result in surface damage. Use mild soap and warm water for cleaning and protecting the life of Chicago Faucet products. For specific operation and maintenance refer to the installation instructions and repair parts documents that are located at <a href="https://www.chicagofaucets.com">www.chicagofaucets.com</a>.

ECAST,<sup>™</sup> from Chicago Faucets, is the line of durable, high-quality brass faucets and fixtures that are designed and manufactured with less than one quarter of one percent (0.25%) total lead content by weighted average. These products are intended for installation where state laws and local codes mandate lead content levels or in any location where lead content is a concern.





2100 South Clearwater Drive
Des Plaines, IL 60018
P: 847/803-5000
F: 847/803-5454
Technical: 800/TEC-TRUE
www.chicagofaucets.com