



P.O. Box 3365 South El Monte, CA 91733 626.444.0541 Fax 626.444.3887 www. Afcon.org

030/040

SWAY BRACE FITTING MODEL K





SIZE - SYSTEM PIPE: Nominal Pipe Size
Steel 1" thru 10" Sch. 10, 40
Allied Dynaflow 1" thru 6"
CPVC 1" thru 3"
Can brace same O.D. - Copper, Plastic, FRP, Ductile and Cast Iron
SIZE - BRACE PIPE: 1" or 1 1/4" Sch. 40
MATERIAL - Carbon Steel.
FINISH - Plain or E.G.
PATENTS - No. 6,508,441
LISTING/APPROVAL -

Horizontal Load Ratings	
Size	UL
1" - 10" Sch. 10, 40	2765
1" - 6" Dynaflow	2765
1" - 3" CPVC	2765

CULUEFE 203A-EX 2625 Listed only for use with other AFCON bracing products. OSHPD OPA-0601-07 See Website.

FUNCTION - Lateral fitting of an *AFCON* sway brace assembly. Sway brace assemblies are intended to be installed in accordance with NFPA 13 and the manufacturer's installation instructions. **INSTALLATION - Per these instructions**

including NFPA 13, 13R and the CPVC manufacturers instructions
Load rating - see chart.
Align brace pipe perpendicular to system pipe.
ASSEMBLY - See drawing.
Combine with proper *AFCON* components.
Insert brace pipe through bores to achieve minimum 1" extension.
Tighten set screws until heads contact the bracket.
FEATURES

* Patented design accommodates piping with common O.D.

* Visual inspection, verifies proper installation.

* Superior load ratings.

ORDERING - Part #, size - system pipe, size - brace pipe and finish.

