



General:

Precast terrazzo one piece products are made of black and white marble chips cast in grey portland cement to produce a compressive strength of not less than 3000 P.S.I., seven days after casting. The terrazzo surface is ground and polished with all air holes and/or pits grouted and the excess removed. Mop service basins are available in custom sizes.

TSB series 12" (305) high. Shoulders shall not be less than 2" (51) wide with 1/2" (13) pitch toward inside. The TSB 100 series includes stainless steel caps on all curbs.

The drain body in mop basins are made of stainless steel cast integrally and provide for a caulked lead connection not less than 1" (25) deep to a 3" (76) pipe.

Installation:

Establish 1/4" (6) clearance between mop service basin and building wall. It is required that the entire area between the mop service basin and the building floor has a 1/2" (13) layer of mortar in order that the mop service basin is level.

Optional stainless steel tiling flanges available.

12" WITH STAINLESS STEEL CAPS ON ALL CURBS						
MODEL	SIZE	APPROX. SHIP WT.	A	B	C	D
TSB-100	24 x 24 x 12	287 lbs/130 kg	24(610)	24(610)	12(305)	12(305)
TSB-300	32 x 32 x 12	435 lbs/197 kg	32(813)	32(813)	16(406)	16(406)
TSB-500	36 x 36 x 12	545 lbs/247 kg	36(914)	36(914)	18(457)	18(457)
TSB-700	36 x 24 x 12	405 lbs/184 kg	36(914)	24(614)	18(457)	12(305)