



Hillsboro 72 x 36 Plus Series Skirted Whirlpool & Soaking Baths

Product Features

- Durable easy-care acrylic construction
- Air activated on/off switch
- Textured slip-resistant bottom
- Eight adjustable color-matched hydro jets, including two lumbar jets
- Integral tile flange
- Heater blank, safety suction and silent air induction
- Available as an invigorating whirlpool and an unjetted soaking bath
- 72" length overall
- 36" width overall
- 19-3/4" height overall
- 50 gallon operating capacity
- 70 gallon total capacity to overflow
- Pre-wired for simple plug-in installation
- Requires a single 115V/20 amp GFCI circuit
- Available in white and biscuit



With Integral Skirt

PFW7236ALSKWH

Recommended Parts

- PF644CP:** 17-22 PVC Cable drain w/ trim - CP
PF644BN: 17-22 PVC Cable drain w/ trim - BN
PF643CP: 17-22 ABS Cable drain w/ trim - CP
PF643BN: 17-22 ABS Cable drain w/ trim - BN

Model Numbers

- PFW7236ALSK** 72" x 36" whirlpool with integral skirt - left hand drain
PFW7236ARSK 72" x 36" whirlpool with integral skirt - right hand drain
PFS7236LSK 72" x 36" soaking bath with integral skirt - left hand drain
PFS7236RSK 72" x 36" soaking bath with integral skirt - right hand drain
SHPRESSHTR Whirlpool heater

Warranty and Codes

This product features a 5-year limited warranty and meets or exceeds the following standards: Whirlpools - IAPMO PS32-84, UL 1975, ANSI Z124.1-95, ASME A112.19.8M-87R(96) and ASME A112.19.7M-95. Baths - ANSI 124.1-95. In an effort to continually improve our products, design changes may periodically be made. Ferguson reserves the right to provide newly designed material to fill any order unless otherwise agreed to in writing.

NOTE: All dimensions and specifications are nominal and may vary $\pm 1/4"$. Use actual products for accuracy in critical situations.

Product Specifications

