



Stik-Ons are 14 gauge steel insulation pins which are permanently staked through 2" x 2" galvanized steel base plates. A pressure-sensitive adhesive backing provides a permanent bond between the Stik-Ons and ductwork.

Stik-Ons can be used to hold all low and medium density insulation and insulation board where the temperature will not exceed 180°F (82°C.).

PRODUCT TECHNICAL DATA

Temperature Range	-30°F (-35°C) - 180°F (82°C)
Application Temperature	Above 40°F (4°C)
Holding Power	3 lbs. per unit
Approximate Shelf Life	2 years @ 70°F (21°C)

APPLICATION

Clean the surface of the duct where contact is to be made, so that it is free of oil, grease, rust, dust, and dirt. Peel off the backing paper and apply firmly to duct. Insulation can be applied immediately. Secure insulation in place using the included companion clips. Bend or cut the unused portion of the pin.

PART #	PRODUCT DESCRIPTION	QTY.
308161	STIK-ONS ¾" 100 (SKC-75)	100/Case
308162	STIK-ONS 1 ¼" 100 (SKC-125)	100/Case
308163	STIK-ONS 1 ¾" 100 (SKC-175)	100/Case
308164	STIK-ONS 2" 100 (SKC-200)	100/Case
308165	STIK-ONS 2 ½" 100 (SKC-250)	100/Case
308166	STIK-ONS ¾" 1,000 (SKM-75)	1,000/Case
308167	STIK-ONS 1 ¼" 1,000 (SKM-125)	1,000/Case
308168	STIK-ONS 1 ¾" 1,000 (SKM-175)	1,000/Case
308169	STIK-ONS 2" 1,000 (SKM-200)	1,000/Case
308170	STIK-ONS 2 ½" 1,000 (SKM-250)	1,000/Case

