


DIMENSIONAL SPECIFICATIONS

LEAD-FREE DOMESTIC BRASS FITTINGS* 125 LB.


SQUARE HEAD CORED PLUG

Part #	Size (IN.)	Approx. Net WT. (LB.)	A	B	C
NL117-08	1/2	0.11	0.54	0.38	0.56
NL117-12	3/4	0.15	0.55	0.44	0.63
NL117-16	1	0.26	0.69	0.50	0.81
NL117-20	1-1/4	0.35	0.71	0.56	0.94
NL117-24	1-1/2	0.45	0.73	0.62	1.13
NL117-32	2	0.60	0.76	0.68	1.31
NL117-40	2-1/2	1.13	1.07	0.74	1.50
NL117-48	3	1.90	1.13	0.80	1.69
NL117-64	4	3.22	1.22	0.92	2.25



SQUARE HEAD SOLID PLUG

Part #	Size (IN.)	Approx. Net WT. (LB.)	A	B	C
NL117A-06	3/8	0.06	0.41	0.31	0.44
NL117A-08	1/2	0.12	0.54	0.38	0.56
NL117A-12	3/4	0.20	0.55	0.44	0.63
NL117A-16	1	0.25	0.69	0.50	0.81
NL117A-20	1-1/4	0.60	0.71	0.56	0.94
NL117A-24	1-1/2	0.76	0.73	0.62	1.13
NL117A-32	2	1.13	0.76	0.68	1.31
NL117A-40	2-1/2	2.26	1.07	0.74	1.50



*Conforms with lead content requirements for lead-free plumbing as defined by the U.S. Safe Drinking Water Act. Certified <0.25 weighted average % lead.



MERIT BRASS

DIRECTING THE FLOW OF *Quality*