



FIRE – RATED ICE MAKER OUTLET BOXES TECHNICAL SPECIFICATION

Job Name _____	Item # _____
Location _____	
Engineer _____	Contractor _____
PO # _____	Tag _____
Representative _____	

SPECIFICATIONS

Oatey Fire-Rated Ice Maker Outlet Boxes can be used in applications requiring supply valves recessed into a fire-rated wall. Unit shall allow for the mounting of supply lines from top or bottom. Unit shall be available with ¼ turn brass ball valves in configurations with and without water hammer arrestors. Adjustable metal support bracket shall be installed on top and bottom of unit for support in stud wall.

APPROVALS AND LISTINGS

Valves	ASME A112.18.1 / CSA B125.1
Water Hammer Arrestors	ASSE 1010
Boxes	IAPMO-Listed, PS-54



ASTM E814

- 1-hour wall: 60 min. (F)
- 1-hour wall: 32 min (T)
- 2-hour wall: 120 min (F)
- 2-hour wall: 85 min (T)

CAN/ULC S115

- 1-hour wall: 60 min. (F/FH)
- 1-hour wall: 32 min (FT/FTH)
- 2-hour wall: 120 min. (F/FH)
- 2-hour wall: 85 min. (FT/FTH)

ADJUSTABLE MOUNTING BRACKET:

- Use nails or screws to secure into stud wall
- **Faceplate:** Snap –on faceplate accommodates up to two layers of 5/8" gypsum


MATERIALS

Outlet Box	Bulk Molding Compound (BMC) Thermoset fire-rated plastic
Adjustable Mounting Bracket	Galvanized Steel
Box Pad	UL Classified FyreWrap Insulation Material

FyreWrap is a registered trademark of Unifrax LLC.

DIMENSIONS

[A]:	Box Width	7.69"	[G]:	Bracket Width	14.25"
[B]:	Box Height	8.69"	[H]:	Bracket Width	23.00"
[C]:	Box Opening Width	5.91"	[I]:	Faceplate Width	8.19"
[D]:	Box Opening Height	5.83"	[J]:	Faceplate Height	8.01"
[E]:	Box Depth	4.20"			
[F]:	Bracket Height	1.22"			



Access BIM/Revit content through www.oatey.com



FIRE – RATED ICE MAKER OUTLET BOXES TECHNICAL SPECIFICATION

PRODUCT SELECTOR

NO HAMMER LOW LEAD			
✓	Product Number	Description	CTN. QTY.
	39117	¼ Turn Brass Ball Valve-Low Lead-Copper Sweat- Standard Pack	1
	39118	¼ Turn Brass Ball Valve-Low Lead- CPVC- Standard Pack	1
	39119	¼ Turn Brass Ball Valve-Low Lead-½" ASTM F1807 PEX- Standard Pack	1
	39120	¼ Turn Brass Ball Valve-Low Lead- ½" ASTM F1960 PEX- Standard Pack	1
	39121	¼ Turn Brass Hammer Ball Valve-Low Lead- Copper Sweat Standard Pack	1
	39122	¼ Turn Brass Hammer Ball Valve-Low Lead- CPVC Standard Pack	1
	39123	¼ Turn Brass Hammer Ball Valve-Low Lead- ½" ASTM F1807 PEX- Standard Pack	1
	39124	¼ Turn Brass Hammer Ball Valve-Low Lead- ½" ASTM F1960 PEX- Standard Pack	1
ACCESSORIES			
	38495	Plain Fire Ice Maker Outlet Box, without faceplate or brackets	6
	38497	Ice Maker Outlet Box Faceplate	6
	38498	Adjustable Metal Support Bracket, 2-pieces	6