


Submitted Model No.: _____
 Specific Features: _____



▲ Designate Proper Finish Suffix

BRIZO®

KITCHEN FAUCETS

- Tresa® Kitchen Collection
- Two Handle Widespread Bridge
- Two Hole Mount

STANDARD SPECIFICATIONS:

- Solid brass with one-piece cast brass waterway.
- 9 27/32" (250 mm) long, 10 21/32" (271 mm) high rigid spout.
- 1/4 turn handle stops.
- Hot and cold stems are interchangeable.
- Control mechanism shall be of the rotating cylinder type with 90° rotation, with replaceable non-metallic seats, operating in stainless steel lined sockets.
- Maximum flow rate 2.2 gpm @ 60 PSI.
- Ceramic disc valving.


WARRANTY

- Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- Indicates compliance to ICC/ANSI A117.1
- Verified compliant with .25% weighted average Pb content regulations.



Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.brizo.com for finish options and product availability.

BSP-K-62436LF Rev. B

Delta Faucet Company

55 E. 111th Street, Indianapolis, Indiana 46280
 350 South Edgeware Road, St. Thomas, ON N5P 4C4
 © 2011 Masco Corporation of Indiana