

Heating Oil Energizer



Specifications

DESCRIPTION

A fuel oil additive which improves combustion efficiency, conserves energy, and reduces fuel oil waste in heating systems.

Each 16-ounce container treats up to 275-gallons of fuel oil.

Cleans strainers, nozzles, pumps and burners, minimizing breakdowns from clogged lines, strainers or nozzles and water-blocked filters. **Power Flow** in fuel oil is a sludge and water dispersant, which prevents waxing and jelling of oil, and inhibits formation of rust in the tank. Product prevents ice formation and freeze-up of fuel oil line assuring a steady flow of fuel in any kind of weather. Reduces soot formation by increasing burner efficiency.

Power Flow also protects fuel oil during summer storage.

SIZES AND PACKING

STOCK NO.	SIZE	PACKING	WEIGHT/CASE
35-302	1 pt.	24	27.0 lbs.

Power
Flow™

Power Flow™ Heating Oil Energizer

APPROVALS AND LISTINGS

N.Y.F.D. Permit No. 210330.

SPECIFIC USES

Use to improve combustion efficiency, conserve energy, reduce fuel waste and clean strainers, filters, nozzles, pumps, and burners. Emulsifies water from condensation.

SPECIFIC APPLICATIONS*

Use **Power Flow** in fuel oil systems.

PHYSICAL PROPERTIES

Specific gravity: 0.8
Solubility in water: Negligible
Boiling point: 317° - 388°F
Appearance/color/odor: Light brown color. Hydrocarbon odor.

WARNINGS OR CAUTIONS

- Read all cautions and directions carefully before using this product.
- **Keep out of reach of children.**
- Harmful or fatal if swallowed. Contains mineral spirits.
- Avoid breathing mist or fumes. Use with adequate ventilation.
- Prolonged exposure to vapors may cause headaches, or dizziness.
- Wash thoroughly after handling.

DIRECTIONS FOR USE

Pour 16-oz. container of **Power Flow** into oil tank before each oil delivery. For tanks larger than 275 gallons use proportionally more **Power Flow**.



MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT,
REQUEST MATERIAL SAFETY DATA SHEET (MSDS) #88

For Delivery by Fax	Call 1-800-942-4636
Internet	See MSDS section of www.herchem.com
Mail	Contact Hercules at address below or any Hercules representative

HMS Hazard Warning 2-2-0-G.

INGREDIENTS **CAS#**

Mineral Spirits 8052-41-3

NJ-T.S.R. #31348300 5022P, 5023P

* For special applications which may not be covered on this or other Hercules literature, please contact Hercules Technical Services Department by phone at 1-800-221-9330 or send a fax to 1-800-333-3456.



Hercules Chemical Company, Inc.

111 South Street, Passaic, NJ 07055-9100

Phone: 800-221-9330 • Fax: 800-333-3456

e-mail: info@herchem.com

<http://www.herchem.com>

