ProPEX[®] Lead-free (LF) Brass Coupling

uponor

Submittal Information Revision A: Jan. 28, 2010

Project Information

| | - | | | | | |
|-----|---|---|---|----|--|--|
| 1oh | Ν | а | m | ۱e | | |

| Job Name: | | |
|--------------------------------|--------------|-------------------|
| Location: | | Part No. Ordered: |
| Engineer: | | Date Submitted: |
| Contractor: | | Submitted By: |
| Manufacturer's Representative: | | Approved By: |
| Technical Data | | |
| Material | C69300 Brass | A |

Product Information and Application Use

ProPEX[®] Lead-free Brass Couplings are available for use in hot and cold domestic potable water systems.¹ Also approved for use in any radiant heating system. The coupling features the Uponor ProPEX Fitting for connections to Wirsbo hePEX[™] tubing or Uponor AquaPEX[®] tubing. Couplings are safe for direct burial in soil.

| \checkmark | Description | Part Number | Α | В | С | D | Weight |
|--------------|--|-------------|-------|--------|--------|--------|--------|
| | ProPEX LF Brass Coupling, 3/8" PEX x 1/2" PEX | LF4543850 | 1.42" | 0.740" | 0.398" | 0.280" | 0.05 |
| | ProPEX LF Brass Coupling, 1/2" PEX x 1/2" PEX* | LF4545050 | 1.54" | 0.740" | 0.398" | N/A | 0.07 |
| | ProPEX LF Brass Coupling, 34" PEX x 34" PEX* | LF4547575 | 2.02" | 1.187" | 0.595" | N/A | 0.13 |
| | ProPEX LF Brass Coupling, $34"$ PEX x 1" PEX* | LF4547510 | 2.25" | 1.345" | 0.795" | 0.595" | 0.16 |
| | ProPEX LF Brass Coupling, 1" PEX x 1" PEX* | LF4541010 | 2.49" | 1.345" | 0.818" | N/A | 0.20 |

Installation

ProPEX Tool and ProPEX Rings (sold separately) are required for connecting the PEX tubing. Use the appropriately sized Uponor ProPEX Ring for tubing connections. For more information, refer to the AquaPEX Professional Plumbing Installation Guide, the AquaSAFE[™] Residential Fire Sprinkler Installation Guide or the Radiant Floor Heating Installation Handbook.

Standards

CAN/CSA B137.5; ASTM F877; ASTM F1960

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

IAMPO 3558; HUD MR 1269; ICC ESR 1099; NSF 14- and 61-certified; U.P. Code, Annex G; *UL 1821; *ULC/ORD C199P

Related Applications

Contact Information

PEX-a Plumbing Systems Uponor Residential Fire Safety Systems Radiant Heating and Cooling Systems Snow and Ice Melting Systems Permafrost Protection Systems Turf Conditioning Systems Uponor, Inc. 5925 148th Street West Apple Valley, MN 55124 USA Phone: (800) 321-4739 Fax: (952) 891-2008 www.uponor-usa.com Uponor Ltd. 2000 Argentia Rd., Plaza 1, Ste. 200 Mississauga, ON L5N 1W1 CANADA Phone: (888) 994-7726 Fax: (800) 638-9517 www.uponor.ca