

ECT work **smart**

Features & Benefits

- Reduce lost time on jobs.
- Use in wet installations.
- Reduce repair interruption time.
- Removable Lead Free brass fittings in sizes ¼" to 2".
- No special installation tools required.
- Joins Copper, CPVC and PEX tubing.
- Quick and easy, removable and reusable installation.
- Ideal for service and repair even on wet lines.
- EPDM o-ring for leak free seals.
- Pre-lubricated for quick installation.
- Potable water & hydronic installation.
- AWWA C800 compliant 1 ¼" to 2".
- 50 Year Warranty*

Applications

Potable water, hot water and chilled water systems*.

Use in underground applications*, as manufactured joints and behind walls without access panels.

 Further details on pressure code compliance and warranty available at www.elkhartproducts.com.

Product Specifications

TECTITE™ fittings are pressure rated at 200 psi (13.8 bar) over a temperature range from 0°F to 250°F (-18°to 121°C) with various liquids and gases.

TECTITE™ fittings are manufactured with an EPDM o-ring seal, a Nylon guide ring and a 316 Stainless Steel grab ring.

Contact EPC's technical representatives for application specific information.

Individually packaged and color coded by size.

1/4"

3/8"










Repair in-line leaks.





Add branch for retro-fit applications.

Pressure Regulators

Made in the USA by Apollo Valves.



Product Portfolio

- Couplings
- Reducer Couplings
- Slip Couplings
- Female Adapters
- Reducing Female Adapters
 90° Female Elbows
- Male Adapters
- Reducing Male Adapters
- 45° Elbows
- 45° Street Elbows
- 90° Elbows
- 90° Reducing Elbows
- 90° Male Elbows
- 90° Drop Ear Elbows
- 90° Hi Ear Elbows



Angle and Straight Stops

- 1/4 turn.
- Compact design.
- Bridge installation on faucet risers.



Water Heater HOSES with ball valves

- Reduce number of connections.
- Flexible for all applications.
- Eliminates 6" code requirement on gas water heaters.
- Stainless steel braided hose.
- Available in 21" length (includes ball valve).

(Hoses carry a 2 year warranty.)



Expansion Tee

- Retrofit expansion tanks.
- No need to drain system for installation.



FAST & SIMPLE Easy push-fit installation. No special tools.

Water Heater Hoses

- Reduce number of connections.
- Flexible for all applications.
- Stainless steel braided hose.
- Available in 20" length.

(Hoses carry a 2 year warranty.)



HEAT FREE

Reduces fire hazard. Utilizes push-fit technology.



CLEAN

No glues, fluxes, or solder needed.



NO CONSUMABLE

MATERIALS

Reduces material cost and storage.



- Reducing Tees
- Slip Tees
- Female Center Slip Tees
- Water Heater Kit
- Water Heater Hose
- Angle Stops
- Straight Stops
- ¼ Turn Faucet Supply Lines
- ¼ Turn Toilet Supply Lines
- Pressure Regulators
- Tube Caps

- Fitting Adapters
- Fitting Reducers
- Dishwasher Elbows
- Garden Hose Elbows
- Water Heater Hose with Ball Valve
- Ball Valves



Another **push solution** from Elkhart Products ...

CopperLOC

- Permanent Push Fit Connection.
- Join Copper, CPVC or PEX.
- Approved for underground application.
- No Tools, No Heat, No Glue, Flux or Solder Required.
- Naturally Lead Free.
 - Available in sizes ½" to 1".
 - Deep insertion depth keeps pipe lengths straight.
 - EPDM o-ring for leak free seals.
 - Pre-lubricated for quick installation.
 - AWWA C800 compliant.
 - 50 Year Warranty*

* Further details on warranty available at www.elkhartproducts.com.



10000

Elkhart Products Corporation

1255 Oak Street, Elkhart, IN 46514



Customer Service (574) 264.3181

For more information visit our website

www.elkhartproducts.com

