



PARTS LIST

ITEM	DESCRIPTION	MATERIAL
1.	BODY	CAST IRON, ASTM A126-B
2.	COVER	CAST IRON, ASTM A126-B
3.	LEVERAGE BRACKET	316 STAINLESS STEEL
4.	BRACKET SCREW	18-8 STAINLESS STEEL
5.	LEVER ARM	316 STAINLESS STEEL
6.	FLOAT ARM	316 STAINLESS STEEL
7.	ORIFICE BUTTON	BUNA-N / 18-8 STAINLESS STEEL
8.	HEX NUT	18-8 STAINLESS STEEL
9.	LOCK WASHER	18-8 STAINLESS STEEL
10.	SPRING PIN	302 STAINLESS STEEL
11.	AIR RELEASE VALVE LINK	316 STAINLESS STEEL
12.	PIVOT LINK	316 STAINLESS STEEL
13.	FLOAT CAP SCREW	18-8 STAINLESS STEEL
14.	BRACKET LOCK WASHER	18-8 STAINLESS STEEL
15.	FLOAT BALL	316 STAINLESS STEEL
16.	COVER BOLTS	STEEL, ASTM A307 (Standard) 316 STAINLESS STEEL (Optional)
17.	COVER NUTS	STEEL, ASTM A307
18.	PIPE PLUG, 1/2"	STEEL
19.	PIPE PLUG, 1"	MALLEABLE IRON
20.	ORIFICE	316 STAINLESS STEEL
21.	O-RING	BUNA-N RUBBER

FIGURE 920 AIR RELEASE VALVES ARE MANUFACTURED AND TESTED IN ACCORDANCE WITH AWWA C512

FIGURE NUMBER	ORIFICE DIAMETER	WORKING PRESSURE	INLET	OUTLET	A (Square)	B	WEIGHT
920	3/16" (4,8mm)	10-150 PSI (69-1034 KPa)	1" NPT or 2" NPT	1/2" NPT	6.38" (162mm)	9.88" (251mm)	24 lbs. (10,9 Kg)
920-H	1/8" (3,2mm)	10-300 PSI (69-2068 KPa)					

GA INDUSTRIES, a VAG Brand		
DATE:	9-06-08	DRAWN BY: WJN
COMPOUND LEVER AIR RELEASE VALVE		
FIGURE 920	DRAWING NO. EAR-7003-W	REV A