



Viega ProPress adapter
Smart Connect technology
Zero Lead

- For use with ASTM B88 and B75 tubing
- Bronze
- Press connection, female pipe thread

Components

EPDM sealing element

Model 2912ZL

P	FPT	Wt [lb]	Quantity	Part No	DG
1/2	3/8	0.083	10	79295	8
1/2	1/2	0.121	10	79300	8
1/2	3/4	0.156	10	79305	8
3/4	1/2	0.147	10	79310	8
3/4	3/4	0.177	10	79315	8
1	1/2	0.179	10	79320	8
1	3/4	0.208	10	79325	8
1	1	0.277	10	79330	8
1	1 1/4	0.370	10	79335	8
1 1/4	1/2	0.220	1	79340	8
1 1/4	1	0.302	1	79345	8
1 1/4	1 1/4	0.391	1	79350	8
1 1/4	1 1/2	0.466	1	79355	8
1 1/2	1 1/4	0.465	1	79360	8
1 1/2	1 1/2	0.560	1	79365	8
2	2	0.781	1	79370	8



Viega ProPress adapter
Smart Connect technology
Zero Lead

- For use with ASTM B88 and B75 tubing
- Copper
- Press connection, female pipe thread

Components

EPDM sealing element

Note

Must be installed with Viega ProPress XL-C rings and V2 actuator.

Model 0912XL

P	FPT	Wt [lb]	Quantity	Part No	DG
2 1/2	2 1/2	1.821	1	20819	8
3	3	2.923	1	20829	8
4	4	4.404	1	20839	8



Viega ProPress adapter
Zero Lead

- For use with Viega ProPress fittings
- Bronze
- Street, female pipe thread

Model 2912.1ZL

FTG (CTS)	FPT	Wt [lb]	Quantity	Part No	DG
1/2	3/8	0.069	5	79425	8
1/2	1/2	0.102	5	79430	8
1/2	3/4	0.140	5	79435	8
3/4	1/2	0.111	5	79440	8
3/4	3/4	0.148	5	79445	8
1	1/2	0.172	1	79455	8
1	1	0.262	1	79450	8
1 1/4	1/2	0.267	1	79460	8
1 1/4	1 1/4	0.402	1	79465	8
1 1/2	1 1/2	0.519	1	79470	8
2	2	0.825	1	79475	8

FTG (CTS) = TEST

Flanges



Viega ProPress adapter flange

2 - pc

Smart Connect technology

Zero Lead

- For use with ASTM B88 and B75 tubing
- Bronze
- Press connection

Components

EPDM sealing element

Model 2959.5ZL

P	BP	BPd	Wt [lb]	Quantity	Part No	DG
1	4	3 1/8	3.292	1	79680	8
1 1/4	4	3 1/2	3.196	1	79685	8
1 1/2	4	3 3/8	4.069	1	79690	8
2	4	4 3/4	5.867	1	79695	8

BP = bolt pattern

BPd = bolt pattern diameter