KOHLER, Faucets

Features

- Brass construction
- Requires and AC power supply
- Single-hole mounting
- Above-counter valve for easy installation and maintenance
- Vandal-resistant aerator
- 24" (610 mm) flexible supply hose for easy installation
- 6-3/16" (157 mm) spout reach
- Stationary gooseneck spout
- Without temperature mixer
- Less drain
- 0.5 gal/min (1.9 l/min) flow rate



ADA CSA B651 OBC

Codes/Standards

ASME A112.18.1/CSA B125.1 NSF 372 DOE - Energy Policy Act 1992 ADA ICC/ANSI A117.1 CSA B651 OBC

All applicable US Federal and State material regulations

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.


Color Code Description

CP Polished Chrome

VS Vibrant® Stainless







Technical Information

All product dimensions are nominal.

Valve body: Machined Brass

Faucet:

Flow rate: 0.5 gal/min (1.9 l/min)

Notes

Install this product according to the installation guide.

A 1-1/4" (32 mm) minimum to 1-1/2" (38 mm) maximum diameter mounting hole is required.

The minimum distance between the back of the faucet spout and the wall must be 1-3/4" (44 mm). This will allow proper clearance for setscrew access.

The maximum distance between the bathroom sink basin edge to the base of the faucet spout must be 1-3/4" (44 mm).

The maximum height of the lip basin should be 3/4" (19 mm).

Product includes rosebud spray aerator. Other aerator styles are available.

This product requires an AC power supply (not included).

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

