


# Anchors

## Drop-in Anchors

- Designed for use in solid concrete.
- Can be used for overhead applications such as suspending cable tray, strut, pipe supports and lighting.
- Flanged (lipped) version installs flush for easy inspection and standardizes rod heights.
- Smooth wall drop-in can be installed flush mounted or below the base material surface.
- UL & FM approved.
- Available in Zinc Plated finish or Stainless Steel.



Drop-In Anchors - Data	1/4"	3/8"	1/2"	5/8"	3/4"
ANSI Drill Bit Size (in.)	3/8	1/2	5/8	7/8	1
Max. Tightening Torque (ft-lbs)	5	10	20	40	80
Thread Size (UNC)	1/4"-20	3/8"-16	1/2"-13	5/8"-11	3/4"-10
Min. Embedment Depth (in.)	1	1 9/16	2	2 1/2	3 3/16
Load Capacity Tension (lbs) *	495	1045	1440	1860	3600
Load Capacity Shear (lbs) *	530	1145	1600	3095	3920

\* Based on concrete compression strength of 4000 psi using applied safety factor of 4.0. For additional loading information contact factory.

Anchors

UPC/Part Number	Catalog Number	Rod Size	Anchor Length	Thread Depth	Box Qty.
-----------------	----------------	----------	---------------	--------------	----------

### Drop-in Anchor - Smooth Wall - Steel

781011 03218	<b>ADI-25</b>	1/4"	1"	7/16"	100
781011 03219	<b>ADI-37</b>	3/8"	1 9/16"	5/8"	50
781011 03220	<b>ADI-50</b>	1/2"	2"	13/16"	50
781011 03221	<b>ADI-62</b>	5/8"	2 1/2"	1 13/16"	25
781011 03222	<b>ADI-75</b>	3/4"	3 3/16"	1 3/8"	10

### Drop-in Anchor - Smooth Wall - Stainless Steel

781011 03223	<b>ADI-25SS4</b>	1/4"	1"	7/16"	100
781011 03224	<b>ADI-37SS4</b>	3/8"	1 9/16"	5/8"	50
781011 03226	<b>ADI-50SS4</b>	1/2"	2"	13/16"	50
781011 03227	<b>ADI-62SS4</b>	5/8"	2 1/2"	1 13/16"	25
781011 03228	<b>ADI-75SS4</b>	3/4"	3 3/16"	1 3/8"	10

### Drop-in Anchor - Flanged - Steel

782051 53297	<b>ADI-25FL</b>	1/4"	1"	7/16"	100
782051 53298	<b>ADI-37FL</b>	3/8"	1 9/16"	5/8"	50
782051 53299	<b>ADI-50FL</b>	1/2"	2"	13/16"	50

UPC/Part Number	Catalog Number	Rod Size	Pin Length	Box Qty.
-----------------	----------------	----------	------------	----------

### Setting Tools

781011 03229	<b>6305</b>	1/4"	39/64"	1
781011 03231	<b>6307</b>	3/8"	61/64"	1
781011 03232	<b>6309</b>	1/2"	13/16"	1
781011 03233	<b>6311</b>	5/8"	15/16"	1
781011 03234	<b>6313</b>	3/4"	16 1/64"	1

Read safety/installation instruction sheets in packages before use.