Honeywell | Safety Products



Product Family XTRATUF® Neoprene Footwear

USA

Slip-resistant Chevron outsoles for sure-gripping traction. Lightweight, shock absorption comfort with cork-cushioned insoles. Easy on and off with smooth, durable fabric linings. Immersed in a special sealant for an XTRATUF "total protection shield." Seamless waterproof construction. Built-in foam insulation. Chevron sole and heel. Steel toe meets ASTM F2413-05 Meets electrical hazard requirements of ASTM F2413-05. Men's Whole Sizes: 3-15

Honeywell SERVUS

Product Numbers & Ordering Information

	Product Numbers	Details		
L	22273G	Servus®, XTRATUF®, Neoprene, Safety Footwear, Steel toe Boot – XTRATUF® – Neoprene – 16 in (40.6 cm) – Copper tan boot – "Safe-Toe" steel toe – Removable insoles – Chevron sole and heel – Men's whole sizes: 3 - 15		
L	22274G	Servus®, XTRATUF®, Neoprene, Safety Footwear, Plain toe Boot – XTRATUF® – Neoprene – 16 in (40.6 cm) – Copper tan boot – Plain toe – Removable insoles – Chevron sole and heel – Men's whole sizes: 5 - 14		

Packaging Information

1 pair per bag, 6 pair per case

Hazardous Materials

NA

Overview

Key Features

• Seamless construction is 100% waterproof to keep workers' feet dry and comfortable • Built-in Polymeric foam insulation provides added warmth • Chevron outsoles provide excellent traction to reduce injuries from slip or fall hazards • Removable insoles and durable fabric linings provide shock absorption and wick away moisture to keep workers' feet dry and comfortable • Neoprene is highly resistant to many organic and inorganic acids, chemicals, and contaminants, prolonging the life of the boot and keeping workers free of harmful irritants

Recommended Industries/Use

 Agriculture 	 Chemical 	 Construction 	 Food Services 	 Municipal Services 	 Oil and Gas
---------------------------------	------------------------------	----------------------------------	-----------------------------------	--	---------------------------------

Transportation
 Utilities

Hazards

_

XTRATUF® Neoprene Footwear

Regulations • Electrical & Arc • Impact • Slip • Splash

- American Society of Testing and Materials ASTM F2413-11
- ANSI Z41-1991 OSHA 1910.136 states; The employer shall ensure that each affected employee uses protective footwear when working in areas where there is a danger of foot injuries due to falling or rolling objects, or objects piercing the sole, and where such employee's feet are exposed to electrical hazards. For more information go to www.osha.gov.
- Canadian Standards Association CAN/CSA Z195-09

Historical Brand

Norcross Safety Products

Warranty Information

Each new Product manufactured and/or sold by NSP is warranted to be free from defects in material and/or workmanship. NSP's responsibility is limited to, at its option repairing or replacing any instrument or part thereof, or issuing a credit, for a period of one year after shipment. NSP's warranty sets forth the limit of NSP's responsibility. ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS, ARE EXCLUDED

Specifications

Construction

• Dipped construction

Height

• 16 inch (40.6 cm)

Insole

· Removable insoles

Insulated

Yes

Material

Neoprene

Metatarsal Protection

None

Sizes

• Men's sizes 3 - 15

Steel Midsole Protection

None

Steel Toe Protection

• Style # 22273G has steel toe protection

Tread

Chevron

Waterproof

• Yes

Technical Support

Technical Support is available Monday through Friday, 8:00 AM to 7:00 PM EST. 1.800.873.5242 hsptechsupport@honeywell.com

© Honeywell International Inc.