TAG:



## Architect/Engineering Specifications:

8" wall mount mixing faucet with rough chrome plated brass body, rough chrome plated brass spout with vacuum breaker, pail hook and garden hose male outlet, compression cartridges with spring checks, lever handles, 1/2" NPT female inlets and upper support rod. Certified to ASME A112.18.1/CSA B125.1 NSF 61-Section 9, NSF 372 and ASSE 1056. Meets ADA ANSI/ICC A117.1 requirements.

Job Name Model Specified Variations Specified Date	Quantity		and the second sec
12 5/8" [321mm]	3 7/8" [99mm]	15 9/16" [396mm] 8 11/16" [220mm] 2 11/16"	
		[68mm]	
Features & Benefits:		Product Compliance:	SP

- 8" wall mount mixing faucet with rough chrome plated brass body
- Vacuum breaker spout with pail hook & garden hose male outlet
- Quarter-turn Eterna compression cartridges with spring • checks to prevent cross flow of water
- Lever handles with color coded indexes
- 1/2" NPT female eccentric inlets with Ø 2" flanges
- Adjustable centers from 7 3/4" to 8 1/4"
- Upper support wall brace
- Material: Rough chrome plated brass body & spout • and chrome plated metal handles

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ASSE 1056 (VB)
- ANSI A117.1 (ADA)

Warranty: One Year (Limited)

## Performance Data:

- Pressure: 20 125 psi
- Temperature: 40 °F 140 °F
- Flow Rate: 12.30 GPM @ 60 psi









## **Optional Handles**

## **Optional Cartridges With Checks**

□ 4" Wrist Action □ Lever (Standard) □ 4-Arm

- □ Quarter-Turn Cerama w/ Check Valve
- □ Quarter-Turn Eterna w/ Spring Check (Standard)



