CPVC Pipe and Fittings Date updated: 1/16/14



SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

CPVC Pipe and Fittings COMMON NAME:

CHEMICAL NAME: Not Applicable. Formulation, see section 3.

Mixture FORMULA:

Mixture, see section 3. **PRODUCT CAS NO.:**

Pressure Pipe and Fittings (CTS) and Chemical Waste Drainage Recommended Use:

Charlotte Pipe and Foundry Company (Plastics Division) SUPPLIER:

4210 Old Charlotte Highway ADDRESS:

Monroe, NC 28110 CITY, STATE, ZIP:

PHONE: +1-704-372-3650 **EMERGENCY PHONE:** +1-704-372-3650

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Toxic and irritating gases and fumes may be given off during burning or thermal decomposition. Avoid generating dust. Fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.



GHS Status This material is hazardous in accordance with the hazard communication standard, 29 CFR

1910.1200

Classification of the substance or mixture Skin irritation - Category 2

Eye irritation - Category 2 B Carcinogenicity - Category 2

GHS label pictogram Health hazard. Signal word

Warning

Hazard statements Causes eye irritation.

Revision Date: 12/11/2013 Page 1 of 6



SAFETY DATA SHEET

Causes skin irritation.

Suspected of causing cancer if inhaled.

Precautionary statements

Obtain special instructions before use. Do not handle until all safety precautions have been Prevention

read and understood. Wear protective breathing gear, such as an N95 or P95 respirator.

Wash skin thoroughly after handling.

If on skin: wash with plenty of water. If in eyes. Rinse cautiously with water for several Response

> minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before

Storage Keep away from intense heat, flames. Store locked up.

Disposal Dispose of in accordance with local regulations.

Skin, eyes, inhalation.

None known.

Hazards not otherwise

classified

Relevant routes of

exposure

Inhalation Melted product is flammable and produces intense heat and dense smoke during burning.

Irritating gases and fumes may be given off during burning or thermal decomposition.

Skin contact Gases and fumes evolved during thermal processing or decomposition can cause skin

irritation.

Dust can cause eye irritation. Gases and fumes evolved during thermal processing or Eye contact

decomposition can cause eye irritation.

No data available. Ingestion

3. HAZARDOUS INGREDIENTS: COMPOSITION/INFORMATION				
INGREDIENT	% WEIGHT	PEL-OSHA	TLV-ACGIH	NIOSH REL
Chlorinated polyvinyl chloride CAS 68648-82-8	>80%	None established for CPVC Particulates not otherwise classified: 15 mg/m3	None established for CPVC Particulates not otherwise classified: 10 mg/m3 (inhalable fraction)	None established
Titanium dioxide CAS 13463-67-7	0-5%	15 mg/m3, total dust	10 mg/m3 TWA	None established

4. FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes.

SKIN CONTACT: Rinse with water. Remove contaminated clothing and shoes. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes before reuse.

INHALATION: If vapors from excessive heating, burning or decomposition products are inhaled: remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular, or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-tomouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing, such as collar, tie, belt, or waistband. In case of inhalation of decomposition

Revision Date: 12/11/2013 Page 2 of 6

CPVC Pipe and Fittings Date updated: 1/16/14



SAFETY DATA SHEET

products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance.

INGESTION: Wash out mouth with water. Remove dentures, if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Loosen tight clothing, such as collar, tie, belt, or waistband.

Notes to physician: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under surveillance for 48 hours

Specific treatments: None known

5. FIRE FIGHTING MEASURES			
FLAMMABLE PROPERTIES			
FLASH POINT: No data.	Decomposition products n	nay be combustible.	
FLAMMABLE LIMITS:	LEL: No Data	UEL: No data	

EXTINGUISHING MEDIA: Use media appropriate for surrounding fire.

FIRE AND EXPLOSION HAZARDS: Not flammable. Thermal decomposition may produce hydrogen chloride, carbon oxides, small amounts of benzene and aromatic and aliphatic hydrocarbons, phosgene.

PROTECTIVE MEASURES FOR FIRE FIGHTERS: Firefighters must wear a NIOSH-approved, full-face piece self-contained breathing apparatus (SCBA) operated in positive pressure mode and full turnout or bunker gear with additional chemical protective clothing as necessary to protect against thermal decomposition products.

SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS: If there is a fire, promptly isolate the scene by removing all persons from the vicinity of the incident. No action shall be taken involving any personal risk or without suitable training

	6. ACCIDENTAL RELEASE MEASURES			
	Personal precautions, protective equipment, and emergency measures			
	For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on		
	For emergency responders	appropriate personal protective equipment. If specialized clothing is required to deal with decomposition products or fumes from burning or excessive heating, take note of information in Section 8 on suitable and unsuitable materials. See also information in "for non-emergency personnel."		
	Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air).		
	Methods and materials for contain	nment and clean-up		
١	Small spill	Avoid dust generation. Vacuum dust with equipment fitted with a HEPA filter		

Revision Date: 12/11/2013 Page 3 of 6



SAFETY DATA SHEET

	and place in a closed, labeled waste container. See Section 1 for emergency contact information.
Large spill	Move containers from spill area. Approach release from upwind. Prevent entry into sewers, waterways, basements, and confined areas. Avoid dust generation. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. See Section 1 for emergency contact information.

7. HANDLING AND STORAGE		
Conditions for safe storage, including any incompatibilities	Store in a dry place away from direct sunlight, heat, and incompatible materials. Avoid intense heat and flames.	
Precautions for safe handling		
Protective measures	Put on appropriate personal protective equipment (see Section 8). Do not handle until all safety precautions have been read and understood. Do not get particles, vapors or fumes in eyes, on skin, or on clothing. Do not ingest. If during normal use, the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator.	
Advice on general occupational hygiene	Employees must wash hands and face before eating, drinking, or smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also section 8 for additional information on hygiene measures.	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation, or other engineering controls to keep worker exposure to airborne contaminants below recommended and statutory limits.

RESPIRATORY PROTECTION: Cutting or sanding this product can generate dust. Used a properly fitted particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product, and the safe working limits of the respirator. A NIOSH-approved N95 single use or P95 multiple use respirator will protect the employee from at least 95% of airborne particles. Follow the respirator manufacture's instructions for proper use. If adhesives or other substances are used with this product, refer to the product manufacturer's safety data sheet for applicable respiratory protective measures.

SKIN PROTECTION: Chemical-resistant, impervious gloves complying with an approved standard should be worn when handling this or any chemical product, if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures containing several substances, the protection time of the gloves cannot be accurately estimated. If adhesives or other substances are used with this product, refer to the product manufacturer's safety data sheet for applicable skin protective measures.

BODY PROTECTION: Personal protective equipment for the body should be selected on the task being performed and the risks involved, and should be approved by a specialist before handling this product. If adhesives or other substances are used with this product, refer to the product manufacturer's safety data sheet for applicable skin protective measures.

EYE/FACE PROTECTION: Safety eyewear complying with an approved standard must be used when a risk assessment indicates this is necessary to avoid exposure to dust. Particulates and dust can be formed when cutting, grinding or sanding this product. If contact with dust or particulates is possible, the following should be worn unless the assessment indicates a higher degree of protection: safety glasses with side shields. If adhesives or other substances are used with this product, refer to the product manufacturer's safety data sheet for applicable eye and face protective measures.

Revision Date: 12/11/2013 Page 4 of 6



9. PHYSICAL AND CHEMICAL PROPERTIES		
APPEARANCE:	Solid. Tan/grey	
ODOR:	Not applicable.	
ODOR THRESHOLD:	Not available	
BOILING POINT:	Not available	
FLASH POINT:	Not applicable	
FLAMMABILITY:	Melted product is flammable.	
AUTOIGNITION TEMPERATURE:	Not applicable	
DECOMPOSITION TEMPERATURE:	Not available	
LOWER/UPPER EXPLOSION LIMITS:	Not available	
VAPOR PRESSURE:	Not available	
LIQUID DENSITY:	Not available	
SPECIFIC GRAVITY:	Approximately 1.4	
MELTING POINT:	Not available	
pH:	Not available	
SOLUBILITY:	Insoluble	
% VOLATILE:	Not available	
VISCOSITY:	Not available	

	10. STABILITY AND REACTIVITY
Stability:	Stable at normal temperatures and pressures.
Reactivity:	Stable at normal temperatures and pressures.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition.
Incompatible materials/conditions:	Consult the Charlotte Pipe and Foundry chemical resistance guide.
Hazardous decomposition products:	Hydrogen chloride, carbon oxides, small amounts of benzene and aromatic and aliphatic hydrocarbons, phosgene.
Hazardous polymerization:	Not available.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY:

No toxicological data is available for the finished product.

Page 5 of 6 Revision Date: 12/11/2013

CPVC Pipe and Fittings Date updated: 1/16/14



SENSITIZATION: No data available. MUTAGENICITY: No data available. **DEVELEPMENTAL**: No data available.

Fertility: No data available.

CARCINOGENICITY: This product contains titanium dioxide, which is classified by the International Agency for Research on Cancer as 2B: possibly carcinogenic to humans. Not listed on the National Toxicology Program Report on Carcinogens or OSHA Subpart Z carcinogen list.

REPRODUCTIVE TOXICITY: Not available

TERATOGENICITY: Not available

SPECIFIC TARGET ORGANS - SINGLE EXPOSURE: Not available

SPECIFIC TARGET ORGANS - REPEATED EXPOSURE: Not available

ASPIRATION HAZARD: Not available

INFORMATION ON THE LIKELY ROUTES OF EXPOSURE:

Potential acute health effects

Eye contact	No known significant effects or critical hazards. Dust can cause eye irritation.
Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects
	may be delayed following exposure.
Skin contact	Skin irritant.
Ingestion	No known significant effects or critical hazards.

Symptoms related to the physical, chemical, and toxicological characteristics

	the state of the s
Eye contact	No data available.
Inhalation	No data available
Skin contact	Adverse symptoms may include irritation.
Ingestion	No data available

Immediate, delayed and chronic effects from short term exposure

Short term exposure

Potential immediate effects	No data available.
Potential delayed effects	No data available

Long term exposure

Potential immediate effects	No data available.
Potential delayed effects	No data available

Potential chronic effects

General	No data available.
Carcinogenicity	May cause cancer. Risk of cancer depends on duration and level of exposure.

Revision Date: 12/11/2013 Page 6 of 6

CPVC Pipe and Fittings Date updated: 1/16/14



SAFETY DATA SHEET

12. ECOLOGICAL INFORMATION

Numerical measures of toxicity

No data available

Persistence and degradability

Does not biodegrade over time.

Bioaccumulative potential

No data available

Mobility in soil

No data available.

Other adverse effects: No known significant or critical hazards.

13. DISPOSAL CONSIDERATIONS

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste should not be disposed of to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste and packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material must be disposed of in a safe way.

14. TRANSPORT INFORMATION		
PROPER SHIPPING NAME:	Not Regulated	
HAZARD CLASS:	Not Regulated	
IDENTIFICATION NUMBER:	Not Regulated	
SHIPPING LABEL:	Not Regulated	
PACKING GROUP:	Not Regulated	

15. REGULATORY INFORMATION		
United States	TSCA 8(b): All ingredients are listed on the U.S. Toxic Substances Control Act inventory.	
	Airborne unbound particles of titanium dioxide of respirable size are listed as being carcinogenic per California Proposition 65.	

16. OTHER INFORMATION

Date of Preparation: 11 December 2013

Key To Acronyms:

Revision Date: 12/11/2013 Page 7 of 6



SAFETY DATA SHEET

CAS: Chemical Abstracts Service CFR: Code of Federal Regulations

HEPA High-Efficiency Particulate Air (filter)

IARC: International Agency for Research on Cancer
LD50 Lethal dose to 50% of exposed laboratory animals

LC50 Lethal concentration to 50% of exposed laboratory animals

LEL: Lower Explosive Limit mg/l Milligrams per liter

NIOSH: National Institute for Occupational Safety and Health (US)

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration (US)

PEL: Permissible Exposure Limit
TSCA Toxic Substances Control Act

TLV: Threshold Limit Value – American Conference of Governmental Industrial Hygienists (ACGIH)

TWA: Time Weighted Average
UEL: Upper Explosive Limit
ug/ m³ Micrograms per cubic meter

DISCLAIMER

NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE FOR THE ABS MATERIALS AS REPRESENTED IN THIS MSDS SHEET. Charlotte Pipe and Foundry assumes no liability whatsoever for the use of or reliance upon this information. The information and data contained in this MSDS has been compiled from information believed to be accurate and is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage, handling and disposal of the product in compliance with applicable federal, state, and local laws and regulations.

Revision Date: 12/11/2013 Page 8 of 6