

# SeeSnake® Reels and Cameras



SeeSnake rM200



rM200 D2A Drum  
Catalog No. 47548



rM200B Reel  
Catalog No. 47528



## RIDGID® SEESNAKE RM200 MAX

With its stow bin and transport system, the SeeSnake rM200 Max camera system was designed with convenience and ergonomics in mind. The rM200 provides different combinations of push cable stiffness and spring flexibility.

### FEATURES

- Interchangeable drum system for on-the-job flexibility.
- Ergonomic handle and wheels for easy transport to and from the job site.
- Provides a convenient docking system for SeeSnake CS6x and CS65x monitors.
- Includes pipe guides for better in-pipe imaging and a stow bin for storing tools at the job site.



**D2A Best Use:** The rM200 D2A configuration uses a moderately stiff 200' (61 m) push cable that provides a good compromise between cable stiffness and ability to navigate turns in the pipe.



**D2B Best Use:** The rM200 D2B includes 165' (50 m) of our stiffest push cable, coupled with a dual-nested spring to navigate tight corners that are not usually passable with such a stiff cable.

### SPECIFICATIONS

SPECIFICATIONS	SeeSnake Max rM200	
	D2A	D2B
Rated Pipe Capacity	1.5" to 8" (38 mm to 203 mm)	2" to 8" (51 mm to 203 mm)
<b>CABLE</b>		
Max Cable Length	200' (61 m)	165' (50 m)
Minimum Bend Radius	2.8" (70 mm)	3.5" (89 mm)
<b>CAMERA</b>		
Style	Self-Leveling	Self-Leveling
Diameter	1" (25 mm)	1" (25 mm)
Length	1" (25 mm)	1" (25 mm)
<b>SONDE</b>		
Frequency	512 Hz	512 Hz
Type	Flexmitter	Flexmitter
<b>DISTANCE MEASUREMENT</b>		
Type	Built-in with Video Overlay	Built-in with Video Overlay
Data Communication	Two-Way	Two-Way

Catalog No.	Description	Weight	
		lb	kg
43248	Reel, SeeSnake MAX rM200A w/D2A Drum	36.4	16.5
47548	Reel, SeeSnake MAX rM200B w/D2B Drum	39.2	17.8

### Accessories

Catalog No.	Description
47793	36 mm Camera Head, 25mm Camera, Pkg of 1
35338	45 mm Pipe Guide, 25mm Camera, Pkg of 2
97462	60 mm Pipe Guide, 25mm Camera, Pkg of 6
46708	85 mm Pipe Guide, 25mm Camera, Pkg of 2
46713	125 mm Pipe Guide, 25mm Camera, Pkg of 2
17553	Spanner Wrench, 25 mm
44038	rM200 Stow Bins
47548	Drum, rM200 D2A NTSC
47538	Drum, rM200 D2B NTSC

### Replacement Parts

Catalog No.	Description
43138	RM200 Camera
43863	200' SeeSnake D2A Push Cable
51813	165' SeeSnake D2B Push Cable
33108	Interconnect Cable

# SeeSnake® Reels and Cameras – Compact Series

**NEW**  
COMING IN 2019



SeeSnake Compact M40 with docked CS6xPak



## RIDGID® SEESNAKE COMPACT M40 WITH TRUSENSE™

The Compact M40 offers similar performance to the SeeSnake Mini in the popular Compact form-factor, combining a small package and all-in-one monitor capability (when used with the SeeSnake CS6xPak monitor). The Compact M40 features TruSense™ technology.



**Best Use:** The Compact M40 has 131' (40 m) of moderately stiff push cable, providing a good compromise between stiffness and the ability to navigate turns.

### FEATURES

- Quick-release docking system for fast, efficient job setup with the SeeSnake CS6xPak monitor.
- Sturdy metal frame provides a solid base that makes it easy to push and retrieve the cable.
- Powerful FleXmitter® sonde has longer range and preserves the camera's ability to make turns.
- High dynamic range (HDR) image sensor offers bright, clear in-pipe imaging in difficult lighting conditions.
- TiltSense Sensor displays the camera's pitch in a pipe on a connected SeeSnake CSx series monitor.
- Included pipe guides center the camera for better in-pipe imaging.

### SPECIFICATIONS

SeeSnake Compact M40	
Rated Pipe Capacity	1.5" to 8" (38 mm to 203 mm)
<b>CABLE</b>	
Max Cable Length	131.2' (40 m)
Minimum Bend Radius	3" (76 mm)
<b>CAMERA</b>	
Style	Self-Leveling TruSense
Diameter	1" (25 mm)
Length	1" (25 mm)
<b>SONDE</b>	
Frequency	512 Hz
Type	FleXmitter
<b>DISTANCE MEASUREMENT</b>	
Type	TruSense Counter
Data-Enabled	Two-Way

Catalog No.	Description	Weight	
		lb	kg
63818	SeeSnake Compact M40 System with 1 Battery and 1 Charger	31.5	14
63813	SeeSnake Compact M40 System	27.7	12.5
63673	SeeSnake Compact M40 (Reel Only)	22	9.9

### Accessories

Catalog No.	Description
47793	36 mm Pipe Guide, 25 mm Camera, Pkg of 1
35338	45 mm Pipe Guide, 25mm Camera, Pkg of 2
97462	60 mm Pipe Guide, 25mm Camera, Pkg of 6
46708	85 mm Pipe Guide, 25mm Camera, Pkg of 2
46713	125 mm Pipe Guide, 25mm Camera, Pkg of 2
63868	Various Pipe Guides, 25mm Camera Head
17553	Spanner Wrench, 25 mm
56813	CS6xPak Digital Recording Monitor
57143	CS6xPak with 2 Batteries and 1 Charger
45363	AC Battery Adapter
44693	18 V Advanced Lithium 2.0 Ah Battery
44698	18 V Advanced Lithium 4.0 Ah Battery
43458	18 V Advanced Lithium Battery Charger

### Replacement Parts

Catalog No.	Description
63853	25 mm Self-Leveling Camera Head - TruSense
63858	130' SeeSnake Compact M40 Push Cable
24703	Kickstand
33108	Interconnect Cable