
## KALLISTA.

## Bellis<sub>™</sub> Traditional Basin Set

## P24600 CODES/STANDARDS APPLICABLE **FEATURES** Solid Brass Construction for Durability and Reliability Specified model meets or exceeds the following: 2ª terSen • 1.5 GPM (5.7 LPM) Flow Rate • ASME A112.18.1/CSA B125.1 **ADA** • Quarter-Turn Washerless Ceramic Disc Valves • NSF 61 Refs EPAC • Two-Handle, Widespread Lavatory Faucet for 8" -• EPA WaterSense® 16" Centers • AB1953 and Bill # S.0152 Certified by IAPMO R&T • Coordinates with the Bellis<sub>™</sub> Collection ADA (lever handle only) 5-1/2" (140 mm) 8" (203 mm) Min 16" (406 mm) Max 5" 2-5/16" (126 mm) (58 mm) 4-1/16" (103 mm) 2-13/16' 2-7/16" 1-3/4" (71 mm) (61 mm) (44 mm) 1-1/2" 7/8" (38 mm) (22 mm) 1-1/8' Max 7-7/8" (28 mm) ITTE (200 mm) COLD 2-1/8" (54 mm) 9 (229 mm) 1 (102 mm) 1-1/4" **Handle Options** (32 mm)

2-15/16" (75 mm) 2-13/16" (71 mm)



P24600-CR

P24600-LV

SPECIFIED MODEL				
Model	Description	Finishes		
P24600-CR	$Bellis_{\scriptscriptstyle \rm TM}$ Traditional Basin Set, Cross Handles	CP Polished Chrome	AD Nickel Silver	AG Brushed Nickel
P24600-LV	$Bellis_{\scriptscriptstyleTM}$ Traditional Basin Set, Lever Handles	CP Polished Chrome	AD Nickel Silver	AG Brushed Nickel

We reserve the right to make revisions without notice in the design of products or in packaging unless this right has specifically been waived at the time the order is accepted.