

Automatic Water Conditioning Systems



The Clack Water Specialist Control

Model TT Twin Tank Stainless Steel Systems WS1 Outdoor / Indoor



The Clack Water Specialist Control

Features solid state microprocessor with easy access settings. The control valve design provides optimum service and backwash rates along with soft water regenerant refill and a double backwash feature. Designed for use with water softening system and/or water filtration system. These systems are fully automatic and self-cleaning

Valve Body

Valve body and meter module are molded from glass-reinforced Noryl for exceptional strength and durability.

Stainless Steel

The outer covering is for U.V protection and algae inhibition on outdoor installations (Optional).

Poly Glass Tanks

Tanks constructed of a high-density polyethylene inner shell, thermal wound with fiberglass. These tanks are totally non-corrosive!

Compact Space Saving

The built-in brine tanks cabinet unit for indoor installations. The valve may be installed in various positions for accessibility.

Model RT Rectangular Built-in Brine Tank Cabinet WS1 Indoor System



Limited Lifetime Warranty

On pressure tanks and brine tanks.

There is a full 3 year warranty on parts

<u>Locally Manufactured by Water Tec</u> of Tucson Inc.

From only the highest quality components at our facility in TUCSON, ARIZONA.

Proven Reliability

THOUSANDS are in service in western United States

Over 40 Year Reputation

Of immaculate customer service satisfaction, integrity and quality!



WATER TEC OF TUCSON

4601 S. 3RD AVE. TUCSON, AZ 85714 PHONE (520)790-1512 FAX (520)745-0549

WATER TEC OF PHOENIX

PHONE (602)288-1422 FAX (520)745-0549

WATER TEC OF NEVADA

PHONE (702)270-0900 FAX (702)270-4350

WEBSITE: www.water-tec.com E-MAIL: questions@water-tec.com AZ ROC# 098794 / 104403 NV ROC# 0055223

WS1 SPECIFICATIONS

MODEL NUMBER	GRAINS CAPACITY	RESIN SIZE	BRINE TANK	SALT LBS. USED PER REGEN. CYCLE	WATER GAL. USED PER REGEN. CYCLE	FLOW RATE
RT 1035 WS1	32,000	10X35	12X24X42	9.5 LBS. *	25 GAL. *	8 GPM
TT 948 WS1	32,000	09X48	18X33	9.5 LBS. *	25 GAL. *	8 GPM
TT 1054 WS1	48,000	10X54	18X40	12 LBS. *	30 GAL. *	10 GPM

^{*} DEPENDING ON INDIVIDUAL WATER CONDITIONS.

SYSTEM INCLUDES A 3/4" OR 1" BYPASS VALVE

OPERATING PRESSURE IS 40 - 90 PSI @ 34F - 110F

OUR SERVICE TECHNICIANS CAN DELIVER AND ADD SALT OR POTASSIUM TO YOUR SYSTEM ON A SCHEDULED ROUTE!

