

Features


- Vitreous china
- Elongated bowl
- Blow-out
- Wall-mount
- Integral seat
- 3.5 gpf (13.2 lpf)
- 1-1/2" rear spud
- 14-3/8" (365 mm) x 11-1/4" (286 mm) water area
- 21-1/2" (546 mm) x 14" (356 mm) x 15-1/4" (387 mm)

WATER-GUARD® BOWL K-4475-C

ADA

CSA B651

OBC



Codes/Standards Applicable

Specified model meets or exceeds the following:

- ADA
- ICC/ANSI A117.1
- CSA B651
- OBC
- ASME A112.19.2/CSA B45.1

Colors/Finishes

- 0: White

Specified Model

Model	Description	Colors/Finishes
K-4475-C	Elongated bowl toilet	□ 0

Product Specification

The elongated, wall-mount, blow-out bowl shall made of vitreous china. Bowl shall have a 1-1/2" rear spud. Bowl shall have 14-3/8" (365 mm) by 11-1/4" (286 mm) water area. Bowl shall be 3.5 gpf (13.2 lpf). Bowl shall have integral seat. Bowl shall be 21-1/2" (546 mm) in length, 14" (356 mm) in width, and 15-1/4" (387 mm) in height. Bowl shall be Kohler Model K-4475-C-0.

Technical Information

Fixture*:	
Configuration	Rear spud, with integral seat, elongated
Water per flush	3.5 gal (13.2 L)*
Spud size	1-1/2"
Passageway	2-5/8" (67 mm)
Water area	14-3/8" (365 mm) x 11-1/4" (286 mm)
Water depth from rim	5-3/8" (137 mm)
Minimum static pressure required	35 psi (241.3 kPa)
Maximum static pressure	80 psi (551.6 kPa)
Maximum flowing pressure required	25 psi (172.4 kPa)
Required supply minimum	25 gpm (94.6 lpm)
* Designed to flush with 3.5 gal (13.2 L) of water when installed with a 3.5 gpf (13.2 lpf) valve.	
Included components:	
Spud	18357

Installation Notes


Install this product according to the installation guide.

Refer to manufacturer and local codes for flush valve requirements.

Will comply with the American Disabilities Act (**ADA**) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with **OBC** Barrier Free requirements when installed per Clause 3.8.3.8 and 3.8.3.9.



Product Diagram