

## 300# Single Jacket All Polyester Fire Hose

**Features:**

- outer construction: single jacket, all polyester
- tube construction: EPDM rubber lining
- proof pressure: **300 PSI**
- service test pressure: **150 PSI** at ambient temperature **70°F (21°C)**
- working pressure: **135 PSI** at ambient temperature **70°F (21°C)**
- 25' and 75' lengths, UL labeled hoses and other threads and configurations are available, contact Dixon®

**Uncoupled**

Size	Bowl	Length	Part #
1½"	1-3/4"	50'	<b>A315-50UC</b>
	1-3/4"	100'	<b>A315-100UC</b>
2"	2-1/4"	50'	<b>A320-50UC</b>
	2-1/4"	100'	<b>A320-100UC</b>
2½"	2-13/16"	50'	<b>A325-50UC</b>
	2-13/16"	100'	<b>A325-100UC</b>
3"	3-3/8"	50'	<b>A330-50UC</b>
	3-3/8"	100'	<b>A330-100UC</b>

**Coupled with female and male expansion ring couplings**

Size	Length	Rocker Lug Aluminum NST (NH) Part #	Rocker Lug Brass NST (NH) Part #	Rocker Lug Aluminum NPSH Part #
1½"	50'	<b>A315-50RAF</b>	<b>A315-50RBF</b>	<b>A315-50RAS</b>
	100'	<b>A315100RAF</b>	<b>A315100RBF</b>	<b>A315100RAS</b>
2"	50'	---	---	<b>A320-50RAS</b>
	100'	---	---	<b>A320100RAS</b>
2½"	50'	<b>A325-50RAF</b>	<b>A325-50RBF</b>	<b>A325-50RAS</b>
	100'	<b>A325100RAF</b>	<b>A325100RBF</b>	<b>A325100RAS</b>
3"	50'	---	---	<b>A330-50RAS</b>
	100'	---	---	<b>A330100RAS</b>