

Pipe Clamps

KWIK-CLIP™ Series

Size Range:

1/2" (15mm) thru 2" (50mm) Copper Tubing or CPVC pipe sizes

3/8" (9.5mm) thru 2 1/8" (54mm) O.D. Tubing sizes

Material: Plastic - Black


Features:

- One piece design greatly reduces installation time.
- No tools required to install.
- Non-metallic design eliminates metal-to-metal contact; preventing galvanic corrosion.
- Easily snaps into channel or onto 3/8"-16 all thread rod.
- Meets UL2043 requirements for plenum rating; and UL94 HB flame rating.
- Working temperature range of -40°F (-40°C) to +275°F (135°C).
- BPIC and BPSC clips can be used with insulation, maintaining an unbroken barrier seal and eliminating sweating.
- BPRC rod clip can be snapped onto 3/8"-16 all thread rod at any location.

Order By: Part number.



Part Number	Copper/CPVC Pipe		O.D. Tubing		Sch.40 Pipe		Approx. Wt./100	
	in.	(mm)	in.	(mm)	in.	(mm)	lbs.	(kg)
BPRC062	1/2"	(15)	5/8"	(15.9)	--	(--)	1.2	(0.54)
BPRC075	5/8"	(16)	3/4"	(19.0)	--	(--)	1.3	(0.59)
BPRC087	3/4"	(20)	7/8"	(22.2)	1/2"	(12.7)	1.4	(0.63)
BPRC100	--	(--)	1"	(25.4)	3/4"	(19.0)	1.5	(0.68)
BPRC112	1"	(25)	1 1/8"	(28.6)	--	(--)	1.6	(0.72)
BPRC125	--	(--)	1 1/4"	(31.7)	1"	(25.4)	1.7	(0.77)
BPRC137	1 1/4"	(32)	1 3/8"	(34.9)	--	(--)	1.8	(0.81)
BPRC150	--	(--)	1 1/2"	(38.1)	--	(--)	2.1	(0.95)
BPRC162	1 1/2"	(40)	1 5/8"	(41.3)	--	(--)	2.3	(1.04)
BPRC200	--	(--)	2"	(50.8)	--	(--)	2.5	(1.13)
BPRC212	2"	(50)	2 1/8"	(54.0)	--	(--)	2.7	(1.22)



KWIK-CLIP™ Series - cont.



Part Number	Copper/CPVC Pipe		O.D. Tubing		Sch.40 Pipe		Approx. Wt./100	
	in.	(mm)	in.	(mm)	in.	(mm)	lbs.	(kg)
BPSC037	1/4"	(6)	3/8"	(9.5)	--	(--)	2.3	(1.0)
BPSC050	3/8"	(10)	1/2"	(12.7)	--	(--)	2.6	(1.2)
BPSC062	1/2"	(15)	5/8"	(15.9)	--	(--)	2.8	(1.3)
BPSC075	5/8"	(16)	3/4"	(19.0)	--	(--)	3.3	(1.5)
BPSC087	3/4"	(20)	7/8"	(22.2)	1/2"	(12.7)	3.9	(1.7)
BPSC112	1"	(25)	1 1/8"	(28.6)	--	(--)	4.5	(2.0)
BPSC137	1 1/4"	(32)	1 3/8"	(34.9)	--	(--)	5.0	(2.2)
BPSC162	1 1/2"	(40)	1 5/8"	(41.3)	--	(--)	5.5	(2.5)



Part Number	Copper/CPVC Pipe		O.D. Tubing		Sch.40 Pipe		Approx. Wt./100	
	in.	(mm)	in.	(mm)	in.	(mm)	lbs.	(kg)
BPIC062	1/2"	(15)	5/8"	(15.9)	--	(--)	2.9	(1.3)
BPIC075	5/8"	(16)	3/4"	(19.0)	--	(--)	2.9	(1.3)
BPIC087	3/4"	(20)	7/8"	(22.2)	1/2"	(12.7)	3.0	(1.4)
BPIC100	--	(--)	1"	(25.4)	3/4"	(19.0)	3.2	(1.4)
BPIC112	1"	(25)	1 1/8"	(28.6)	--	(--)	3.3	(1.5)
BPIC125	--	(--)	1 1/4"	(31.7)	1"	(25.4)	3.4	(1.5)
BPIC137	1 1/4"	(32)	1 3/8"	(34.9)	--	(--)	3.5	(1.6)
BPIC150	--	(--)	1 1/2"	(38.1)	--	(--)	3.8	(1.7)
BPIC162	1 1/2"	(40)	1 5/8"	(41.3)	--	(--)	4.0	(1.8)
BPIC200	--	(--)	2"	(50.8)	--	(--)	4.2	(1.9)
BPIC212	2"	(50)	2 1/8"	(54.0)	--	(--)	4.4	(2.0)



Insert in channel.



Twist into place.



Lay tubing/pipe into clip.



Snap clip closed.

All dimensions in charts and on drawings are in inches. Dimensions shown in parentheses are in millimeters unless otherwise specified.