

PATCHING CEMENT

PSPC50LB

Proselect Patching Cement is a cementitious mortar for structural repairs of holes, voids and cracks in concrete and masonry surfaces.

Product Features

- Minimizes downtime on restoration projects
- Easy to use...just add water.
- Fast initial setting (9 to 11 minutes)
- Ready to use in approximately 60 minutes
- Excellent freeze / thaw resistance for durability
- Each bag covers approximately 10 ft² at 1/2 inch depth
- Packaged in a lined 50 lb. water resistant bag
- Accepts foot traffic after 1 hour
- Can be extended with SSD pea gravel

Uses include but are not limited to

- Restoration of existing concrete, masonry, steel or wood surfaces
- Precast panels, steps, columns and beams, concrete pipe
- Above or below grade, interior or exterior, horizontal or vertical...even overhead repairs
- Construction faults in formed walls, snap-tie or spreader holes, cracks, honeycombs
- Curbs, walkways, handrails, cornices, lintels, sills
- Can be used under water.

Product Specifications

PSPC50LB Patching Cement 50 lb. bag

Shelf life: 1 year from date of manufacture

CALIFORNIA PROP 65 WARNING: This product may contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. **Wash Hands After Handling.**