



PYRAMEX
Perform At Your Peak™



Ztek® ANSI CE CSA



Integrated nosepiece
Soft, non-slip rubber temple tips provide non-binding fit

Part No.	Lens and Temples
S2510S ●●●	Clear
S2510ST ●●●	AF Clear H2X
S2514S ●●●	1.5 IR Filter
S2514S are designed for peripheral personnel and visitors who are NOT exposed to direct IR radiation.	
S2515S ●●●	Coffee
S2520S ●●●	Gray
S2520ST ●●●	AF Gray H2X
S2530S ●●●	Amber
S2540S ●●●	Orange
S2550SF ●●●	5.0 IR Filter
S2560S ●●●	Infinity Blue
S2560SF ●●●	3.0 IR Filter
S2560ST ●●●	AF Infinity Blue H2X
S2565S ●●●	Purple Haze
S2570S ●●●	Silver Mirror
S2575S ●●●	Blue Mirror
S2580S ●●●	I/O Mirror
S2590S ●●●	Gold Mirror
S25ARCS ●●●	Arc

S25ARCS are great for use under the welding helmet – allows welder to see his work clearly without suffering “welders flash burn” from surrounding welders.

Mini Ztek ANSI CE CSA



Mini Ztek has all the great features of Ztek in a design better suited for slimmer facial sizes

Part No.	Lens and Temples
S2510SN ●●●	Clear
S2510SNT ●●●	AF Clear H2X
S2517SN ●●●	Pink
S2520SN ●●●	Gray
S2530SN ●●●	Amber
S2560SN ●●●	Infinity Blue
S2575SN ●●●	Blue Mirror
S2580SN ●●●	I/O Mirror

Ztek® Readers ANSI CE CSA



Part No.	Lens and Temples
S2510R15 ●●●	Clear +1.5 Mag
S2510R20 ●●●	Clear +2.0 Mag
S2510R25 ●●●	Clear +2.5 Mag
S2514R15 ●●●	1.5 IR Filter +1.5 Mag
S2514R20 ●●●	1.5 IR Filter +2.0 Mag
S2520R15 ●●●	Gray +1.5 Mag
S2520R20 ●●●	Gray +2.0 Mag
S2520R25 ●●●	Gray +2.5 Mag



There's more to see at
PyramexSafety.com

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●) and Canadian (CSA Z94.3) (●) standards.

Ztek® Readers

General Specifications

Weight: 21 gm
 PD: 68 mm
 Bridge: 13 mm
 Lens base: 10 curve
 Lens size diagonal: 64 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.5 mm
 Overall length (lens - tip): 154 mm
 Overall width (hinge - hinge): 137.5 mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple tips: polyvinyl chloride (PVC)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: polycarbonate
 Side shields: polycarbonate

Part No.	Lens Marking	Frame Marking	Temple Marking
S2510R15	P Z87 + U6	+ 1.50	P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
S2510R20	P Z87 + U6	+ 2.00	P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
S2510R25	P Z87 + U6	+ 2.50	P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
S2514R15	P Z87 + R 1.5 S	+ 1.50	P Z87 - 2+
S2514R20	P Z87 + R 1.5 S	+ 2.00	P Z87 - 2+
S2520R15	P Z87 + U6 L2.5	+ 1.50	P Z87 - 2+
S2520R20	P Z87 + U6 L2.5	+ 2.00	P Z87 - 2+
S2520R25	P Z87 + U6 L2.5	+ 2.50	P Z87 - 2+

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 R: IR filter
 S: Special purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L2.5: 29% max visible light

Frame Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 - 2: Rx
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

