

Double Clapper Siamese Connections



Features:

- double drop clapper with (2) pin lug swivel inlets provides required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply (250 GPM minimum per inlet)
- exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes
- maximum operating pressure: **175 PSI at 70°F (21°C)**
- finish: -P polished or -C polished chrome plated
- UL listed and FM approved


back outlet

Outlet Female NPT Thread	(2) Inlets Female Thread	Branding	Cast Brass Part #
4"	2½" NST(NH)	AutoSprinkler	DCS4025F
		AutoSprinkler	DCS4025F-P
		AutoSprinkler	DCS4025F-C
		StandPipe	DCS4025F-SP
		No Branding	DCS4025F-NB
6"	2½" NST(NH) 2½" NST(NH)	AutoSprinkler	DCS4030F
		AutoSprinkler	DCS4030NYFD
6"	2½" NST(NH) 2½" NST(NH)	AutoSprinkler	DCS6025F
		StandPipe	DCS6025F-SP



Dimensions

Size	A	B
4" x 2½" x 2½"	9 ⁵ / ₈ "	12¼"
6" x 2½" x 2½"	10¼"	11¾"
4" x 3" x 3"	10"	12½"
6" x 3" x 3"	10 ³ / ₈ "	12½"



bottom outlet


Outlet Female NPT Thread	(2) Inlets Female Thread	Branding	Cast Brass Part #
4"	2½" NST(NH)	AutoSprinkler	90DCS4025F
		AutoSprinkler	90DCS4025F-P
		AutoSprinkler	90DCS4025F-C
		StandPipe	90DCS4025F-SP
		No Branding	90DCS4025F-NB
6"	2½" NST(NH) 2½" NST(NH)	AutoSprinkler	90DCS4030F
		AutoSprinkler	90DCS4030NYFD
6"	2½" NST(NH) 2½" NST(NH)	AutoSprinkler	90DCS6025F
		StandPipe	90DCS6025F-SP
6"	3" NYFD 3" NYFD	AutoSprinkler	90DCS6030NYFD
		AutoSprinkler	90DCS6030NYFDSP



polished

Dimensions

Size	A	B	C
4" x 2½" x 2½"	11¾"	9 ⁵ / ₈ "	7¼"
6" x 2½" x 2½"	11¾"	10¼"	7¼"
4" x 3" x 3"	12½"	10 ¹ / ₈ "	7½"
6" x 3" x 3"	12¼"	10 ⁷ / ₈ "	7¼"



- special threads, branding and finishes are available, consult Dixon® for information
- replacement swivels can be ordered on page 792