

SUBMITTAL INFORMATION

Ultra-Tite Coupling - (C16-xx-U-NL style)



FEMALE IRON PIPE THREAD BY ULTRA-TITE FOR POLYETHYLENE PIPE (PEP)



DESCRIPTION				Approx.	Part	✓ SUBMITTED
FEMALE IRON PIPE	UT FOR PEP	LENGTH	O.D. RANGE	WT. LBS	Number	ITEM(S)
3/4"	3/4"	2-27/32"	1.045 - 1.110	.8	C16-33-U-NL	
3/4"	1"	2-59/64"	1.329 - 1.399	.8	C16-34-U-NL	
1"	1"	3-1/16"	1.329 - 1.399	.9	C16-44-U-NL	

FEATURES

- All brass that comes in contact with potable water conforms to AWWA Standard C800 (UNS No. C89833)
- The product has the letters "NL" cast into the main body for lead-free identification
- Certified to NSF/ANSI Standard 61 and NSF/ANSI Standard 372 where applicable
- Brass components that do not come in contact with potable water conform to AWWA Standard C800 (ASTM B62 and ASTM B584, UNS No. C83600, 85-5-5-5)
- · Hexagonal wrench flats provided for proper installation

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167 www.fordmeterbox.com

03/28/14

_	•		
Sı	ıhr	nitted	1 Rv