

Faucet Aerators Dual Thread 2.2 GPM

Product Features

- Patented 3-screen slotted design provides a splash-free stream, well aerated and soft touch
- Standard flow
- 1 pice construction
- 2.2 gpm flow rate Not for use in California or any state/area that requires lower flow rates
- · Rubber washer.
- Mini Counter Display: 12 tubes of 6 faucet aerators

Technical Data

Materials: Housing Brass Construction

Washer EPDM

Max working temperature: 150°F Max working Pressure: 125 psi

Model Number

PFX113174



PFX113174

Product Specifications



PROFLO Aerators

ITEM	DESCRIPTION	GPM(LPM)		
PFX113174	Dual Thread. 15/16" (23.8mm) Male X 55/64" (21.8mm) Female Chrome Plated	2.2 (8.3279) @60 PSI		

DIMENSIONS

	MALE THREAD		FEMALE THREAD		A		В		C	
ITEM	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM
PFX113174	15/16	23.8	55/64	21.8	15/16	23.8	15/16	23.8	3/4	19

Warranty and Codes

Listed to ANSI 112.18.1M and NSF 61. Lead free, complies with reduction of lead in drinking water act. This PROFLO product carries a 1-year limited warranty.



Compliant with lead content requirements