

Dual Scale Pressure Gauge

Product Features

- Accuracy : $\pm 2.5\%$ of Span (Grade B ANSI B40.1)
- 1/4" NPT Brass Connection (Lower Mount)
- Black Corrosion Resistant Paint Steel Case with Flat Glass Window
- Dual Scale : psi / kPa
- CRN Registered : 0F13895.5C
- Bourdon Tube Style (except for PFPG5L)
- Operating Temperature : Ambient: -4°F to 140°F (-20°C to 60°C)
Media : max. 158°F (70°C)

Application

- For use with air, gas or water applications and medium that will not clog the connection port or corrode the copper alloy.
(Examples: hydraulic and pneumatic systems, pumps, compressors, water systems and regulator)



PFPG100K

✓ For Submittal	Model Number	Description	Diameter Face (in)	psi	kPa
	*PFPG15K1	Pressure Gauge	2 in	0-15#	0-100#
	PFPG30K	Pressure Gauge	2 in	0-30#	0-200#
	PFPG60K	Pressure Gauge	2 in	0-60#	0-400#
	PFPG100K	Pressure Gauge	2 in	0-100#	0-700#
	PFPG160K	Pressure Gauge	2 in	0-160#	0-1100#
	PFPG200K	Pressure Gauge	2 in	0-200#	0-1400#
	PFPG300K	Pressure Gauge	2 in	0-300#	0-2000#
	**PFPG5L	Pressure Gauge	2-1/2 in	0-5#	0-35#
	PFPG30L	Pressure Gauge	2-1/2 in	0-30#	0-200#
	PFPG60L	Pressure Gauge	2-1/2 in	0-60#	0-400#
	PFPG100L	Pressure Gauge	2-1/2 in	0-100#	0-700#
	PFPG160L	Pressure Gauge	2-1/2 in	0-160#	0-1100#
	PFPG200L	Pressure Gauge	2-1/2 in	0-200#	0-1400#
	PFPG300L	Pressure Gauge	2-1/2 in	0-300#	0-2000#
	PFPG100N	Pressure Gauge	3-1/2 in	0-100#	0-700#
	PFPG200N	Pressure Gauge	3-1/2 in	0-200#	0-1400#
	PFPG300N	Pressure Gauge	3-1/2 in	0-300#	0-2000#



****PFPG5L**



***PFPG15K1**

* 1/10 lb Increments

** Internal design: diaphragm capsule

Warranty and Codes

This PROFLO product carries a 1-year limited warranty.