



# Wellworth® | K-4467-U

Toilet tank, 1.28 gpf

## Features

- Left-hand Polished Chrome trip lever
- Insuliner® tank liner minimizes condensation on the tank
- Combines with the K-4199 bowl to create a complete K-3999-U Highline toilet
- Combines with the K-5393 bowl to create a complete K-5481-U Highline toilet
- Coordinates with other products in the Wellworth collection
- KOHLER's canister flush valve harnesses the natural force of gravity and optimizes flushing performance
- 1.28 gpf (4.8 lpf)
- Class Five® canister optimizes the flow out of the tank, harnessing gravity and the natural, powerful reducing cascade of water to increase the power and effectiveness of the flush



## Sustainability



## Available Colors/Finishes

*Color tiles intended for reference only.*

- |    |             |
|----|-------------|
| 0  | White       |
| 96 | Biscuit     |
| 7  | Black Black |



1-800-4KOHLER (1-800-456-4537)  
Kohler Co. reserves the right to make revisions without notice to product specifications.  
For the most current specification sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada.  
4-15-2026 3:49 - US-CA

THE BOLD LOOK  
OF **KOHLER**

## Codes/Standards

*Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.*



ASME A112.19.2/CSA B45.1  
EPA WaterSense®

---

## Technical Information

|             |                    |
|-------------|--------------------|
| Flush Type: | Class Five         |
| Flush Rate: | 1.28 gpf (4.8 lpf) |

---

## Recommended Products/Accessories

K-23726 Drain treatment

---

## Warranty

*See website for detailed warranty information.*

KOHLER® Toilets and Seats Limited Warranty



---

## Installation

- Supply line sold separately
- 

## Installation Notes

*Install this product according to the installation instructions.*

Product dimensions are nominal and may vary per ASME A112.19.2 tolerances.

