

	<b>MINI-MC®</b> ½" CTS - 1" IPS (16mm - 34mm)		<b>1LC</b> ½" CTS - 1" IPS (16mm - 34mm)				<b>2LC</b> ½" CTS - 2" IPS (16mm - 60mm)		<b>2CU</b> ½" CTS - 2" IPS (16mm - 60mm)	
MODELS	1" IPS Machine	32mm Machine	1" IPS Machine		32mm Machine					
<b>Input Voltage</b>	N/A	N/A	100-120V, 50/60Hz, 1Ph	220-240V, 50/60Hz, 1Ph	100-120V, 50/60Hz, 1Ph	220-240V, 50/60Hz, 1Ph	100-120V, 50/60Hz, 1Ph	220-240V, 50/60Hz, 1Ph	100-120V, 50/60Hz, 1Ph	220-240V, 50/60Hz, 1Ph
<b>Part Number</b>	<b>CTS07901</b>	<b>CTS08001</b>	<b>ACTS23301</b>	<b>ACTS23302</b>	<b>ACTS23303</b>	<b>ACTS23304</b>	<b>A217201</b>	<b>A217202</b>	<b>A200101</b>	<b>A200102</b>
<b>WEIGHT</b>			<b>WEIGHT</b>				<b>WEIGHT</b>		<b>WEIGHT</b>	
<b>Machine</b>	3.5 lbs (1.6 Kg)		3.6 lbs (1.63 Kg)				23 lbs (10.4 Kg)		28 lbs (12.7 Kg)	
<b>Facer</b>	Sold separately		1.8 lbs (0.82 Kg)				7.9 lbs (3.54 Kg)		7.9 lbs (3.54 Kg)	
<b>Heater</b>			2.5 lbs (1.13 Kg)				7.24 lbs (3.28 Kg)		7.24 lbs (3.28 Kg)	
<b>POWER</b>			<b>POWER</b>				<b>POWER</b>		<b>POWER</b>	
<b>Heater</b>			100 Watt				800 Watt		800 Watt	
<b>Facer</b>	Sold separately		Hand-operated with ¾" square drive				Hand-operated		Hand-operated	
<b>Plug Type</b> ①			A	C	A	C	A	C	A	C
<b>DIMENSIONS</b> ②			<b>DIMENSIONS</b> ②				<b>DIMENSIONS</b> ②		<b>DIMENSIONS</b> ②	
<b>Length</b>	7.75" (197mm)		5.25" (133mm)				13" (330mm)		11" (279mm)	
<b>Width</b>	3.75" (95mm)		4.25" (108mm)				14" (357mm)		20" (508mm)	
<b>Height</b>	11.5" (292mm)		7.5" (191mm)				15" (381mm)		16" (406mm)	
<b>INCLUDES</b>			<b>INCLUDES</b>				<b>INCLUDES</b>		<b>INCLUDES</b>	
	Fusion machine and screw/driver kit		Fusion machine, heater, facer, insulated heater sling, ratchet wrench, screw/driver kit and case				Fusion machine, heater, facer, insulated heater/facer stand and screw/driver kit		Fusion machine, heater, facer, insulated heater/facer stand and screw/driver kit	

**SOCKET TOOLING KITS**

½" CTS - 4" IPS (16mm - 125mm)

MODELS	<b>ASW19101</b>	<b>ASW19102</b>	<b>ASW19201</b>	<b>ASW19202</b>	<b>ASW19301</b>	<b>ASW19302</b>	<b>ASW19401</b>	<b>ASW19402</b>	<b>ASW19501</b>	<b>ASW19502</b>	<b>ASW19601</b>	<b>ASW19602</b>
<b>Pipe Size Range</b>	¾" - 2" IPS		½" CTS - 2" IPS		3" & 4" IPS		¾" & 1 ¼" IPS		16mm - 63mm		75mm - 125mm	

<b>HEATER</b>													
<b>Heater Size</b>	2"		2"		4"		2"		2"		4"		
<b>Voltage Requirements</b>	100-120V, 50/60Hz, 800 Watt, 1Ph	200-240V, 50/60Hz, 800 Watt, 1Ph	100-120V, 50/60Hz, 800 Watt, 1Ph	200-240V, 50/60Hz, 800 Watt, 1Ph	100-120V, 50/60Hz, 1,200 Watt, 1Ph	200-240V, 50/60Hz, 1,200 Watt, 1Ph	100-120V, 50/60Hz, 800 Watt, 1Ph	200-240V, 50/60Hz, 800 Watt, 1Ph	100-120V, 50/60Hz, 800 Watt, 1Ph	200-240V, 50/60Hz, 800 Watt, 1Ph	100-120V, 50/60Hz, 800 Watt, 1Ph	200-240V, 50/60Hz, 800 Watt, 1Ph	
<b>Plug Type</b> ①	A	C	A	C	A	C	A	C	A	C	A	C	

<b>ADAPTERS &amp; CUTTERS</b>												
<b>Socket Fitting Holder(s)</b>	2" IPS		2" IPS		3" and 4" IPS		N/A		2" IPS		3" and 4" IPS	
<b>Shears/Cutters</b>	1.7" & 2.4" OD capacity						4" Plastic pipe cutter		1.7" & 2.4" OD capacity		4" Plastic pipe cutter	
<b>Heater Adapters Included</b>	¾" IPS, 1" IPS, 1 ¼" IPS, 1 ½" IPS, 2" IPS		½" CTS, ½" IPS, ¾" CTS, ¾" IPS, 1" CTS, 1" IPS, 1 ¼" CTS, 1 ¼" IPS, 1 ½" IPS, 2" IPS		3" IPS, 4" IPS		¾" IPS, 1 ¼" IPS		16mm, 20mm, 25mm, 32mm, 40mm, 50mm, 65mm		75mm, 90mm, 110mm, 125mm	

<b>INCLUDES</b>													
Tool box, heater, heater adapters, tubing shears/cutters, chamfer tools/depth gauges, screw/driver kit and cold ring tools													

① See **Reference** section for plug types

② See **Reference** section for more detailed dimensions

	<b>PIT BULL® 14</b> 1" IPS - 4" DIPS (32mm - 110mm)		<b>PIT BULL 26</b> 2" IPS - 6" DIPS (63mm - 180mm)		
MODELS	6" DIPS Machine		180mm Machine		
<b>Input Voltage</b>	100-120V, 50/60Hz, 1Ph	200-240V, 50/60Hz, 1Ph	100-120V, 50/60Hz, 1Ph	200-240V, 50/60Hz, 1Ph	200-240V, 50/60Hz, 1Ph
<b>Part Number</b>	<b>A430101</b>	<b>A430102</b>	<b>A708502</b>	<b>A708505</b>	<b>A708504</b>
<b>WEIGHT</b>			<b>WEIGHT</b>		
<b>Machine</b>	35 lbs (15.9 Kg)		50 lbs (22.7 Kg)		
<b>Facer</b>	21.56 lbs (9.78 Kg)		32 lbs (14.5 Kg)		
<b>Heater</b>	10 lbs (4.53 Kg)		14 lbs (6.4 Kg)		
<b>POWER</b>			<b>POWER</b>		
<b>Minimum Power Req.</b>	3 kVA, 2.5 kW		3 kVA, 2.5 kW		
<b>Heater</b>	1,200 Watt		1,200 Watt		
<b>Facer</b>	0.5 HP, 7 Amp	0.5 HP, 3.5 Amp	0.5 HP, 7 Amp	1.6 HP, 5 Amp	
<b>Plug Type</b> ①	A	C	A	C / M	C / M
<b>DIMENSIONS</b> ②			<b>DIMENSIONS</b> ②		
<b>Length</b>	15.5" (394mm)		15.4" (391mm)		
<b>Width</b>	16.5" (419mm)		19.7" (500mm)		
<b>Height</b>	31.8" (808mm)		30.4" (773mm)		
<b>INCLUDES</b>			<b>INCLUDES</b>		
	Fusion machine, heater, facer, insulated heater stand and screw/driver kit		Fusion machine, heater, facer, insulated heater stand, facer stand, 6" IPS/180mm insert set and screw/driver kit		

① See **Reference** section for plug types

② See **Reference** section for more detailed dimensions

## INCREASE PRODUCTIVITY ON THE JOB

Pair a manual machine stand and two PolyPorters® with either a Pit Bull 14 or 26 to save time and money. Combine these labor-saving tools in one convenient package.



<b>14 PACKAGE</b>		<b>26 PACKAGE</b> (6" DIPS)		<b>26 PACKAGE</b> (180mm)	
120V	240V	120V	240V	240V	
<b>A441501</b>	<b>A441502</b>	<b>A708402</b>	<b>A708405</b>	<b>A708404</b>	

	<b>SIDEWINDER®</b> Saddle Fuse 4" IPS and Smaller Branch Saddles			
MODELS	Chain Clamp	Compact Chain Clamp	Jaw Clamp	Compact Jaw Clamp
<b>1500 PSI</b>	<b>ASW00110</b>	<b>ASW00120</b>	<b>ASW00130</b>	<b>ASW00140</b>
<b>1000 PSI</b>	<b>ASW00111</b>	<b>ASW00121</b>	<b>ASW00131</b>	<b>ASW00141</b>
<b>600 PSI</b>	<b>ASW00112</b>	<b>ASW00122</b>	<b>ASW00132</b>	<b>ASW00142</b>
<b>300 PSI</b>	<b>ASW00113</b>	<b>ASW00123</b>	<b>ASW00133</b>	<b>ASW00143</b>
<b>WEIGHT</b>				
<b>Machine</b>	28 lbs (13 Kg)	27 lbs (12 Kg)	26 lbs (11.7 Kg)	25 lbs (11 Kg)
<b>DIMENSIONS</b>				
<b>Length</b>	12.5" (318mm)	12.5" (318mm)	7.75" (203mm)	7.75" (203mm)
<b>Width</b>	12.5" (318mm)	12.5" (318mm)	10.5" (267mm)	10.5" (267mm)
<b>Height</b>	26.5" (673mm)	21.4" (546mm)	28" (711mm)	23" (584mm)
<b>INCLUDES</b>				
Fusion machine, 3" pivot master and screw/driver kit				