



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 1/22/10

## DAP® KWIK SEAL PLUS® Premium Kitchen and Bath Adhesive Sealant with MICROBAN® Antimicrobial Product Protection

- Waterproof
- Easy clean-up
- Excellent durability and adhesion
- Fights the growth of stain-causing bacteria, mold and mildew on the sealant
- Sealant stays cleaner between cleanings
- Crack-Proof guarantee

**Packaging:** 5.5 fl. oz. (162 mL) and 10.1 fl. oz. (300 mL)  
**Color:** Higher Gloss Brighter White, Higher Gloss Biscuit  
**UPC Number:** 70798 18510, 70798 18526, 70798 18539, 70798 18519, 70798 18539, 70798 18526

### Company Identification:

**Manufacturer:** DAP Products Inc., 2400 Boston St., Ste. 200, Baltimore, Maryland 21224  
**Usage Information:** Call 1-888-DAP-TIPS or visit [dap.com](http://dap.com) & click on "Ask the Expert"  
**Order Information:** 800-327-3339  
**Fax Number:** 410-534-2650

### Product Description:

**DAP® KWIK SEAL PLUS®** Kitchen and Bath Adhesive Sealant with Microban® Antimicrobial Product Protection fights the growth of stain and odor-causing bacteria, mold and mildew on the sealant. The advanced Microban® Antimicrobial Product Protection neutralizes bacterial and fungal growth where it lives and breeds. This means that the sealant is easier to keep clean and stays cleaner between cleanings. This specially formulated siliconized latex formula provides excellent adhesion and flexibility for a waterproof seal. **DAP® KWIK SEAL PLUS®** provides easy water clean-up and is low in odor. Provides a high gloss sheen even when dry. Paintable with both latex and oil-based paints. Backed by a Crack-Proof Guarantee.

### Suggested Uses:

*Ideal for Caulking and Sealing:*

- |                 |                         |                           |
|-----------------|-------------------------|---------------------------|
| • Tubs          | • Sinks                 | • Backsplashes            |
| • Shower Stalls | • Countertops           | • Toilets                 |
| • Fixtures      | • Repairing loose tiles | • Other cracks and joints |

*Outstanding Adhesion to:*

- |                    |                   |              |
|--------------------|-------------------|--------------|
| • Ceramic Tile     | • Plastic Tile    | • Glass      |
| • Porcelain        | • Cultured Marble | • Wood       |
| • Metal            | • Drywall         | • Fiberglass |
| • Painted Surfaces |                   |              |

**Performance Characteristics:**

- Micorban<sup>®</sup> protection fights the growth of stain and odor-causing bacteria, mold and mildew on the sealant.
- Paintable with latex or oil based paints. Allow to dry two or more hours before painting. Longer in low temperatures or high humidity.
- Some cleaning products may affect the performance of this product.
- Easy water clean-up.
- Provides a waterproof seal.

**Surface Preparation & Application:**

1. Surface must be clean, dry and free of all old caulk, dirt, dust and grease. Rubbing alcohol is recommended for removing soap film and soil.
2. Remove cap (from tube). Cut nozzle at a 45° angle to desired bead size. Load into caulking gun if using the 10.1 fl. oz. cartridge.
3. Joint width should not exceed 3/8". If joint depth exceeds 3/8", use backer rod material.
4. Fill gap with sealant, pushing sealant ahead of nozzle.
5. For a neat finish, smooth bead of sealant with a finishing tool.
6. Clean up excess sealant with a damp cloth before it skins over (15 minutes.)
7. Reseal tube/cartridge for future use.

***For Best Results:***

- Apply in temperatures above 40°F.
- Not for continuous underwater use.
- Allow sealant to dry at least 2 hours (longer in cool or humid conditions) before painting with a latex or oil-based paint.
- Allow sealant to dry fully (at least 24 hours) before exposing to water and moisture.
- Store product away from extreme heat or cold.

**Physical & Chemical Characteristics:**

Tooling Time:	10 Minutes
Tack Free Time:	30 Minutes
Paintability:	Yes
Odor:	Very Mild
Consistency:	Smooth and Creamy
Vehicle:	Acrylic Polymer
Volatile:	Water
Flash Point:	None
Filler:	Calcium Carbonate
Density:	1.05 ± 0.01
Solids:	59% ± 1.0% by weight
Weight per Gallon:	8.8 ± 0.05 lbs/gallon
Temperature Service Range:	-30°F to 180°F
Temperature Application Range:	40°F to 100°F
Freeze Thaw Stability:	Passes 5 Cycles
Shelf Life:	12 Months
Coverage:	5.5 fluid ounces: 30 linear ft. at a 3/16" diameter bead or 2 average size bathtubs. 10.1 fluid ounces: 56 linear feet or 4 average size bathtubs.
MSDS No:	00010025001

**Clean Up:**

Before curing, remove excess sealant with a damp cloth. After product has cured, excess sealant must be cut or scraped away.

**Safety:**

See product label or Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at [www.dap.com](http://www.dap.com) or by calling 1-888-DAP-TIPS.

**Crack-Proof Guarantee:**

DAP will, within 1 year from the date of purchase, replace this product or refund sales price, if this product mildews, cracks, peels or separates when used as directed. Return used container and sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, Maryland 21224. DAP will not be liable for incidental or consequential damage.

