

Small Landscape Accent



PROJECT:
TYPE:
ORDERING #:
COMMENTS:


FEATURES

4.375"

- · 4" Accent Light For Cross-Lighting, Spotlighting, or Grazing
- · Cast Aluminum Housing
- Tempered Convex Glass Lens
- 8" of Usable 200° 18 AWG Wire Leads
- 4000V (4KV) Pulse Rated Medium Base Porcelain Socket
- Max Lamping 35W PAR20 Metal Halide or 50W PAR20 / R20 Incandescent (Not Included)
- Remote Ballast Required for HID Lamping
- ANSI / UL Listed Wet Location
- Housing Includes a 1-Year Warranty From Date of Purchase

MOUNTING ACCESSORIES

• HID Ballasts Include a 2-Year Warranty From Date of Purchase



ORDERING INFORMATION

EXAMPLE: 15231BKT (Product # & Finish)

PRODUCT REMOTE BALLAST SPECS **FINISH** 15231 AZT - Textured Above Ground Ballast 15MH535AZT - Single 35W MH 120V ANSI M130 Architectural - Dimensions: 6.375" W x 9.5" L x 5.25" D Bronze - Stamped Steel w/ Textured Architectural Bronze Thermoset Powder Coat Finish Copper Wrapped Core & Coil w/ HPF 105° High Heat Capacitor & Long Range Ignitor Rated For -20° F Starting 0.5" & 0.75" Trade Size Combination Knockouts For Conduit Entry - Mounting Screws & Anchors Included - UL Listed For US & Canada **BKT** - Textured **Black** In Ground Ballast **15IGMHS35AZ -** Single 35W MH 120V ANSI M130 Dimensions: 9.625" Diameter x 12" Height Reinforced Composite w/ Molded-in

Ribs to Prevent Ground Shift

- 0.5" NPSM Removable Plug

For Direct Fixture Mount & Remote

Two Threaded 0.75" NPT Entries

- Re-Enterable Encapsulant 3M 8882

- One Piece, Molded Silicone O-Ring

to Ballast Cannot Exceed 15 Feet

Please Note: Maximum Distance From Lamp

Quick Disconnect Ballast

w/ Bracket Handle

Mount Application

- Captive & Gasketed

For Conduit Attachment

Potting Compound Included

- CSA Listed For US & Canada

15276BK - A Fast. One-Step Connector - Made of Impact / Corrosion Resistant PVC

- 2.250" Inside Diameter to

Accomodate Conduits of Different Sizes

- Accepts .50 NPSM Thread

- Designed For 120V Line Voltage Landscape Lighting, Eliminating Need For Above or Below Ground Boxes

Built-in Stabilizer Removes **Need For Concrete**

15601AZT - Cast Aluminum Surface Mounting Flange w/ Bronze Finish, Neoprene Gasket For Watertight Seal

15601BKT - Cast Aluminum Surface Mounting Flange w/ Black Finish, Neoprene Gasket For Watertight Seal

15601BBR - Cast Brass Surface Mounting Flange, Neoprene Gasket For Watertight Seal

2.39" W


5.56" H

Mounting Bracket Corrosion Resistant Cast

Aluminum Alloy w/ Baked Thermoset Bronze Powder Coat Finish

Mounting Bracket

Aluminum Alloy w/ Baked Thermoset Black Powder Coat Finish



LENS ACCESSORIES

15620BKT - PAR20 / R20 Medium Hood - 3.32" in Length



15628AZT - PAR20 / R20 Long Hood - 7.45" in Length 15628BKT - PAR20 / R20 Long Hood - 7.45" in Length




15623BL - Small Blue Lens Filter Tempered Glass to Resist

- Heat & Impact
- Enhances Color to Bring Out The True Rich Greens of Foliage



15637BK - 45° Small Perforated Shield - Expanded Aluminum Shield w/ HighTemperature Black Finish







15609BKT - Junction Box

- Corrosion Resistant Cast



NOTES

For Warranty Information. please visit www.landscapelighting.com We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.