

**NIBCO**

1516 Middlebury Street  
Elkhart, IN 46516-4740

**Phone:** 574.295.3000 • **Fax:** 800.234.0557

**E-Mail:** [info@nibco.com](mailto:info@nibco.com) • **Web site:** [www.nibco.com](http://www.nibco.com)

## Material Number NL99HXE, T-595-Y-66-LF - Ball Valve - Lead-Free\*, Three-Piece, Full Port, Stainless Steel Trim

The NIBCO® ball valve provides ease of operation with quarter-turn (90 degrees) open to close. The lead-free ball valve provides bubble-tight shutoff at 600 PSI. Please refer to NIBCO technical data sheet, valve selection guides and catalog for engineering and installation information. Choose NIBCO® valves for the most specified, versatile and economical valve option in commercial and residential applications. NIBCO® valves are backed by the NIBCO INC. 5-year 125% limited warranty.



### Specifications

<b>UPC Code</b>	039923320247
<b>Type</b>	Ball Valve
<b>Valve Size</b>	2 1/2 in
<b>Body Material</b>	Lead Free Silicon Bronze
<b>Seat Material</b>	PTFE
<b>Seal Material</b>	PTFE
<b>Stem Material</b>	Stainless Steel
<b>Operation Type</b>	CS Standard Lever Handle
<b>Connection Type</b>	T -- Female NPT Thread (FIPT)
<b>Ball Material</b>	Stainless Steel

<b>Description</b>	T-595Y-66-LF 21/2 THRD FULL PT 3-PC SS T
<b>Valve Ball Body Type</b>	Three-Piece
<b>Turns / Operation</b>	Quarter-Turn
<b>Valve Ball Port Style</b>	Full Port
<b>Weight</b>	21.068 lb